


HIGH TRACTION FOR DRIVABILITY IN SEVERE CONDITIONS



ON/OFF APPLICATION



11R22.5 11R24.5

The 16-ply rated **CI-637** is a tire proven to work well on and off-highway supporting extra-heavy loads common in the logging and mining industries. The deep 32/32 inch tread depth provides long tread life and excellent traction. The CI-637 is mud and snow rated and is equipped with an intricate five-rib block design specifically shaped to minimize squirm for stability and even wear.



OPEN-SHOULDER TREAD DESIGN

creates additional biting edges for optimal traction.



STONE DEFENSE FEATURES

effectively minimize rock and pebble packing to protect the belt package and casing from stone drilling.



CURB GUARD protects the casing from in-service damage.



CUT AND CHIP RESISTANT TREAD COMPOUND is comprised of a much softer compound that is flexible,

preventing puncture during ride on rough terrain.

Size	Ply-Rating/ Load Range	I Itom #	Single Load Index	Load	OD (in)	S.L.R. (in)	Buff Radius	Overall Width (in)	RPM	Depth	Weight		Max Speed -	Single Load Limit		Dual Load Limit	
											lbs.	kg	(MPH)	lbs./PSI	kg/kPa	lbs./PSI	kg/kPa
11R22.5	16/H	62569937	148	145	42.5	1938.0	26	11.5	489	32/32	129	59	68	6940@123	3150@850	6395@123	2900@850
11R24.5	16/H	62569968	149	146	44.4	20.7	26	11.1	468	32/32	143	65	62	7160@120	3250@830	6610@120	3000@830