

CUV/SUV TOURING VARIABLE-CONDITIONS TIRE

Toyo Celsius CUV offers year-round versatility plus winter-weather safety in one. This variable-conditions tire offers better ice and snow traction than a typical all-season tire and longer tread life than a winter tire. Celsius stops up to 31 feet shorter on snow than a typical all-season tire[^] plus it's backed by a 60,000-mile warranty.

MILEAGE WARRANTY*

60,000 miles

POPULAR FITMENTS

Audi Q5
Chevrolet Equinox
Ford Edge
Honda CR-V
Subaru Outback
Toyota RAV4

UTQG

500 A A
520 A A



Three-Peak Mountain Snowflake qualified for severe snow conditions.

VARIABLE SIPE DENSITY

- Inside Tread: Higher sipe density for excellent traction on ice and snow.
- Outside Tread: Lower sipe density for stability and traction on wet and dry roads.

SNOW CLAWS

- Improves deep snow traction.
- Increases block rigidity for better ice and wet traction.

SLUSH GROOVES

- Increases traction by evacuating slush and snow.

MULTI-WAVE SIPES

- Minimizes irregular wear for a smooth, quiet ride.
- Improves braking on icy, wet, and dry roads.



[^]Performance claim based upon commissioned third-party test results. Snow braking test conducted on 255/55R18 tires from 30 to 0 mph. Individual results may vary. For a copy of the test report, write to Toyo Tire U.S.A. Corp., P.O. Box 6052, Cypress, CA 90630.

*See toyotires.com for details.

SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD (LBS) SINGLE	MAX PRESSURE (PSI)	REVS PER MILE
16	235/70R16	106H	SL	BSW	129920	6.0-(7.0)-8.0	30	11.3	29	9.4	2094	51	717
	225/55R17	101V	XL	BSW	128000	6.0-(7.0)-8.0	28	11.0	26.8	9.2	1819	50	776
17	225/60R17	99V	SL	BSW	128020	6.0-(6.5)-8.0	28	11.1	27.6	9	1709	51	752
	225/65R17	102H	SL	BSW	128040	6.0-(6.5)-8.0	31	11.2	28.5	9	1874	51	729
	235/55R17	103V	XL	BSW	128010	6.5-(7.5)-8.5	31	11.1	27.2	9.6	1929	50	765
	235/60R17	102H	SL	BSW	128030	6.5-(7.0)-8.5	31	11.2	28.1	9.4	1874	51	739
	235/65R17	108V	XL	BSW	128050	6.5-(7.0)-8.5	33	11.3	29.1	9.4	2205	50	715
	P245/65R17	105H	SL	BSW	128060	(7.0) -8.5	33	11.3	29.5	9.8	2039	51	704
	P265/70R17	115S	SL	BSW	129910	7.0-(8.0)-9.0	40	11.3	31.7	10.7	2679	44	656
	225/55R18	98V	SL	BSW	129860	6.0-(7.0)-8.0	29	11.0	27.8	9.2	1653	51	749
18	235/55R18	100V	SL	BSW	128070	6.5-(7.5)-8.5	31	11.1	28.1	9.6	1764	51	738
	235/60R18	107V	XL	BSW	128090	6.5-(7.0)-8.5	33	11.2	29.1	9.4	2149	50	714
	P235/65R18	104H	SL	BSW	128120	6.5-(7.0)-8.5	32	11.3	30	9.4	1984	51	692
	245/60R18	105H	SL	BSW	128100	(7.0) -8.5	33	11.3	29.6	9.8	2039	51	703
	255/55R18	109V	XL	BSW	128080	7.0-(8.0)-9.0	36	11.3	29	10.4	2271	50	716
	P255/65R18	109H	SL	BSW	128130	7.0-(7.5)-9.0	38	11.3	31.1	10.2	2271	51	669
	265/60R18	110V	SL	BSW	128110	7.5-(8.0)-9.5	40	11.3	30.5	10.7	2337	51	681
	265/65R18	114T	SL	BSW	129890	7.5-(8.0)-9.5	39	11.3	31.5	10.7	2601	44	659
275/65R18	116T	SL	BSW	129900	7.5-(8.0)-9.5	40	11.3	32.1	11	2756	44	647	
19	225/55R19	99V	SL	BSW	129870	6.0-(7.0)-8.0	31	11	28.8	9.2	1709	51	722
	235/50R19	99H	SL	BSW	128140	6.5-(7.5)-8.5	32	11.1	28.3	9.6	1709	51	734
	235/55R19	105V	XL	BSW	128170	6.5-(7.5)-8.5	33	11.1	29.2	9.6	2039	50	712
	P245/55R19	103H	SL	BSW	128180	7.0-(7.5)-8.5	34	11.2	29.6	10	1929	51	701
	255/50R19	107V	XL	BSW	128150	7.0-(8.0)-9.0	35	11.3	29.1	10.4	2149	50	714
	P255/60R19	108H	SL	BSW	128200	7.0-(7.5)-9.0	40	11.3	31.1	10.2	2205	51	669
	265/50R19	110H	XL	BSW	128160	7.5-(8.5)-9.5	37	11.3	29.5	10.9	2337	50	704
	275/55R19	111V	SL	BSW	128190	7.5-(8.5)-9.5	40	11.3	30.9	11.2	2403	51	672
20	P235/55R20	102H	SL	BSW	128230	6.5-(7.5)-8.5	32	11.1	30.2	9.6	1874	51	689
	P245/50R20	102V	SL	BSW	128210	7.0-(7.5)-8.5	34	11.2	29.7	10	1874	51	700
	255/50R20	109V	XL	BSW	129850	7.0-(8.0)-9.0	37	11.3	30.1	10.4	2271	50	691
	265/50R20	107V	SL	BSW	128220	7.5-(8.5)-9.5	38	11.3	30.5	10.9	2149	51	682
	275/55R20	117V	XL	BSW	129880	7.5-(8.5)-9.5	42	11.3	31.9	11.2	2833	50	651

LIGHT TRUCK / SUV / CUV

LT

Speed rated "H" = 130mph, "V" = 149mph. "SL" = Standard Load, "XL" = Extra Load, "BSW" = Black Sidewall. Bold designates measuring rim width. **Inflated dimensions.

For the latest tire information, please visit toyotires.com.

TOYO TIRES®