

## VARIABLE-CONDITIONS TIRE

Toyo Celsius offers year-round versatility plus winter-weather safety in one. This variable-conditions tire offers better ice and snow traction than a typical all-season tire and longer tread life than a winter tire. Celsius stops up to 14 feet shorter on snow and eight feet shorter on ice than a typical all-season tire<sup>^</sup> plus it's backed by a 60,000-mile warranty.

### MILEAGE WARRANTY\*

60,000 miles

### POPULAR FITMENTS

Ford Taurus  
Honda Civic  
Hyundai Sonata  
Nissan Altima  
Toyota Camry  
Volkswagen Jetta

### UTQG

400 A B - 440 A A



Three-Peak Mountain Snowflake qualified for severe snow conditions.

### VARIABLE SIPE DENSITY

- Inside Tread: Higher sipe density for excellent traction on ice and snow.
- Outside Tread: Lower sipe density for traction on wet and dry roads.

### SNOW CLAWS

- Improves deep snow traction.
- Increases block rigidity for better ice and wet traction.

### SLUSH GROOVES

- Increases traction by evacuating slush and snow.

### MULTI-WAVE SIPES

- Minimizes irregular wear for a smooth, quiet ride.
- Improves braking on icy, wet, and dry roads.



<sup>^</sup>Performance claim based upon commissioned third-party test results. Test conducted on 215/60R16 tires. Snow braking from 30 to 0 mph; ice braking from 15 to 0 mph. Individual results may vary. For a copy of the test report, write to Toyo Tire U.S.A. Corp., P.O. Box 6052, Cypress, CA 90630.

\*See [toyotires.com](http://toyotires.com) for details.



WHEEL DIA.	TIRE SIZE	LOAD/SP. SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX. LOAD (LBS)	MAX. PRESSURE (PSI)	REGS PER MILE
14	185/65R14	86H	SL	BSW	128240	5.0-( <b>5.5</b> )-6.5	16	10.7	23.5	7.4	1168	51	885
	185/60R15	84T	SL	BSW	128250	5.0-( <b>5.5</b> )-6.5	17	10.6	23.7	7.4	1102	44	875
	185/65R15	88H	SL	BSW	128270	5.0-( <b>5.5</b> )-6.5	17	10.7	24.4	7.4	1235	51	850
	195/60R15	88H	SL	BSW	128260	5.5-( <b>6.0</b> )-7.0	19	10.7	24.2	7.9	1235	51	858
	195/65R15	91H	SL	BSW	128280	5.5-( <b>6.0</b> )-7.0	19	10.8	25	7.9	1356	51	831
	205/65R15	94H	SL	BSW	128290	5.5-( <b>6.0</b> )-7.5	20	11.0	25.5	8.2	1477	51	816
	205/70R15	96T	SL	BSW	128300	5.0-( <b>6.0</b> )-7.0	22	11.3	26.3	8.2	1565	44	789
	205/75R15	97S	SL	BSW	128330	5.0-( <b>5.5</b> )-7.0	23	11.3	27.1	8	1609	44	766
	215/70R15	98T	SL	BSW	128310	5.5-( <b>6.5</b> )-7.0	24	11.3	26.9	8.7	1653	44	773
	225/70R15	100T	SL	BSW	128320	6.0-( <b>6.5</b> )-7.5	26	11.3	27.4	9	1764	44	757
235/75R15	105S	SL	BSW	128340	6.0-( <b>6.5</b> )-8.0	29	11.3	28.9	9.3	2039	44	720	
15	185/60R16	86H	SL	BSW	221290	5.0-( <b>5.5</b> )-6.5	19	10.6	24.7	7.4	1168	51	840
	205/55R16	91H	SL	BSW	128350	5.5-( <b>6.5</b> )-7.5	20	10.7	24.9	8.4	1356	51	835
	205/60R16	92H	SL	BSW	128360	5.5-( <b>6.0</b> )-7.5	21	10.8	25.7	8.2	1389	51	809
	205/65R16	95H	SL	BSW	128400	5.5-( <b>6.0</b> )-7.5	22	11.0	26.5	8.2	1521	51	785
	215/55R16	97H	XL	BSW	221380	6.0-( <b>7.0</b> )-7.5	24	10.2	25.3	8.9	1609	50	822
	215/60R16	95H	SL	BSW	128370	6.0-( <b>6.5</b> )-7.5	24	11.0	26.1	8.7	1521	51	795
	215/65R16	98T	SL	BSW	128410	6.0-( <b>6.5</b> )-7.5	25	11.1	27	8.7	1653	44	769
	225/60R16	98H	SL	BSW	128380	6.0-( <b>6.5</b> )-8.0	25	11.1	26.6	9	1653	51	781
	235/60R16	100T	SL	BSW	128390	6.5-( <b>7.0</b> )-8.5	27	11.2	27.1	9.4	1764	44	767
	235/65R16	103T	SL	BSW	128420	6.5-( <b>7.0</b> )-8.5	28	11.3	28	9.4	1929	44	741
16	205/45R17	88V	XL	BSW	129520	6.5-( <b>7.0</b> )-7.5	21	10.1	24.3	8.1	1235	50	857
	205/50R17	93V	SL	BSW	128890	5.5-( <b>6.5</b> )-7.5	21	10.1	25.1	8.4	1433	50	827
	215/45R17	91V	XL	BSW	129450	<b>(7.0)</b> -8.0	21	10.2	24.6	8.4	1356	50	843
	215/50R17	91H	SL	BSW	128430	6.0-( <b>7.0</b> )-7.5	22	10.8	25.5	8.9	1356	51	814
	215/55R17	98V	SL	BSW	128940	6.0-( <b>7.0</b> )-7.5	25	10.2	26.3	8.9	1653	50	790
	215/60R17	96H	SL	BSW	128440	6.0-( <b>6.5</b> )-7.5	25	11.0	27.2	8.7	1565	51	765
	225/45R17	94V	SL	BSW	128920	7.0-( <b>7.5</b> )-8.5	23	10.3	25	8.9	1477	50	832
	225/50R17	98V	SL	BSW	128930	6.0-( <b>7.0</b> )-8.0	23	10.3	25.9	9.2	1653	50	802
	225/55R17	101V	XL	BSW	129120	6.0-( <b>7.0</b> )-8.0	26	10.3	26.8	9.2	1819	50	776
	225/60R17	99H	SL	BSW	128450	6.0-( <b>6.5</b> )-8.0	26	11.1	27.6	9	1709	51	752
17	235/45R17	97V	XL	BSW	128990	7.5-( <b>8.0</b> )-9.0	23	10.5	25.4	9.3	1609	50	819
	235/55R17	103V	SL	BSW	128910	6.5-( <b>7.5</b> )-8.5	28	10.5	27.2	9.6	1929	50	765
	245/45R17	99V	XL	BSW	129000	7.5-( <b>8.0</b> )-9.0	24	10.6	25.7	9.6	1709	50	809
	215/45R18	93V	XL	BSW	129580	<b>(7.0)</b> -8.0	22	10.2	25.6	8.4	1433	50	811
	225/40R18	92V	SL	BSW	128880	7.5-( <b>8.0</b> )-9.0	23	10.3	25.1	9.1	1389	50	828
	225/45R18	95V	XL	BSW	128950	7.0-( <b>7.5</b> )-8.5	24	10.3	25.9	8.9	1521	50	801
	225/50R18	95V	SL	BSW	129180	6.0-( <b>7.0</b> )-8.0	25	10.3	26.9	9.2	1521	51	773
	225/60R18	100H	SL	BWS	221390	6.0-( <b>6.5</b> )-8.0	29	11.1	28.6	9	1764	51	726
	235/40R18	95V	XL	BSW	129510	8.0-( <b>8.5</b> )-9.5	23	10.5	25.4	9.5	1521	50	818
	235/45R18	98V	XL	BSW	128980	7.5-( <b>8.0</b> )-9.0	26	10.5	26.3	9.3	1653	50	789
18	235/50R18	101V	XL	BSW	128960	6.5-( <b>7.5</b> )-8.5	27	10.5	27.3	9.6	1819	50	761
	235/55R18	100V	SL	BSW	128970	6.5-( <b>7.5</b> )-8.5	28	10.5	28.1	9.6	1764	51	738
	245/40R18	97V	XL	BSW	129460	8.0-( <b>8.5</b> )-9.5	24	10.6	25.7	9.8	1609	50	808
	245/45R18	100V	XL	BSW	128900	7.5-( <b>8.0</b> )-9.0	27	10.6	26.7	9.6	1764	50	779
	245/55R18	103W	SL	BSW	129360	7.0-( <b>7.5</b> )-8.5	29	10.0	28.6	10	1929	51	726

Speed rated "S" = 112mph, "T" = 118mph, "H" = 130mph. "SL" = Standard Load, "BSW" = Black Sidewall. Bold designates measuring rim width. \*\*Inflated dimensions.

# SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD (LBS)	MAX PRESSURE (PSI)	REVS PER MILE
19	245/40R19	98V	XL	BSW	129470	8.0-( <b>8.5</b> )-9.5	27	10.6	26.7	9.8	1653	50	777
	245/45R19	102V	XL	BSW	129200	7.5-( <b>8.0</b> )-9.0	31	10.6	27.7	9.6	1874	50	751
	245/50R19	105V	XL	BSW	129140	7.0-( <b>7.5</b> )-8.5	33	10.6	28.7	10	2039	50	724
	255/35R19	96V	XL	BSW	129600	8.5-( <b>9.0</b> )-10.0	28	10.7	26	10.2	1565	50	798
	255/40R19	100V	XL	BSW	129350	8.5-( <b>9.0</b> )-10	31	10.7	27	10.2	1764	50	768
	255/45R19	104V	XL	BSW	129130	8.0-( <b>8.5</b> )-9.5	32	10.7	28.1	10	1984	50	740
20	245/40R20	99V	XL	BSW	129590	8.0-( <b>8.5</b> )-9.5	28	10.6	27.7	9.8	1709	50	750
	245/45R20	103V	XL	BSW	129160	7.5-( <b>8.0</b> )-9.0	32	10.6	28.7	9.6	1929	50	725

PASSENGER CAR

P