

Legend:

| | | | |
|---|---|---|---|
|  |  |  |  |
| 3G Casing | SmartWay Verified | With TPMS Sensor | Retread Available |

PRODUCT FEATURES ABOVE ONLY APPLY TO PRODUCTS IF THE MATCHING ICON IS DARKENED.

Conti HAC 3

Construction All-Position

GOODS PEOPLE CONSTRUCTION




PRODUCT DATA



| TIRE SIZE | LOAD RANGE | ARTICLE NUMBER | TREAD DEPTH (32nds) | MAX SPEED (MPH) | STATIC LOADED RADIUS | | OVERALL INFLATED DIAMETER | | OVERALL INFLATED WIDTH | | LOADED SECTION WIDTH | | APPROVED RIM(S) | MINIMUM DUAL SPACING | | REVS PER UNIT | | TIRE WEIGHT | | MAX. LOAD @ INFLATION | |
|-------------|------------|----------------|---------------------|-----------------|----------------------|-----|---------------------------|------|------------------------|-----|----------------------|-----|---------------------|----------------------|-----|---------------|-----|-------------|----|------------------------|--------------------|
| | | | | | IN | MM | IN | MM | IN | MM | IN | MM | | IN | MM | MI | KM | LB | KG | LBS, PSI (KG, KPa) | LBS, PSI (KG, KPa) |
| | | | | | | | | | | | | | | | | | | | | | |
| 385/65R22.5 | L | 05652000000 | 22 | 68 | 196 | 498 | 42.0 | 1067 | 14.8 | 376 | 15.9 | 404 | 11.75, 12.25 | N/A | N/A | 493 | 306 | 169 | 77 | 9920, 130 (4500, 900) | N/A |
| 425/65R22.5 | L | 05652010000 | 24 | 68 | 20.8 | 529 | 44.8 | 1138 | 16.6 | 421 | 17.9 | 454 | 13.00, 12.25, 14.00 | N/A | N/A | 462 | 287 | 185 | 84 | 11400, 120 (5150, 830) | N/A |

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Aggressive on/off-road tread design combined with enhanced cap/base compounds for **improved mileage and traction.**



Rugged 4-belt tread package resists impacts, bruises and penetrations for improved casing durability.



Minimal stone retention due to **self-cleaning tread pattern** and groove geometry for enhanced retreadability.



Increased sidewall gauge for improved resistance against curbing, cuts and abrasions.



Embedded with **TPMS Active Sensor** Technology.

Intelligent Tire | Equipped with TPMS Sensor

- **Accurate, real-time** tire pressure and temperature readings
- **Sensor lasts 6 years / 400,000 miles** to minimize disruptions
- **Sensor provides true casing temperature** allowing preventive actions that make your tire last longer
- **Avoids valve damage and air leaks** by mounting on the inner liner



To get connected with one of our Digital Tire Monitoring Solutions, visit www.continental-truck.com.

Applications: Wide base, all-position fitment for on/off-road, mixed service applications such as cement mixers.

CONSTRUCTION