




Dynapro AT2



For aggressive all-terrain driving

The best on/off-road tire for 4x4 vehicles, the Dynapro AT2 employs a tough pattern design and block structure to overcome any road.

 Meets the severe snow service requirement of the U.S. Tire Manufacturer's Association (USTMA)


Traction


Low noise


Off-road


Mileage


Snow traction

30 DAY
FREE TRIAL

60K
warranty

ROAD HAZARD
WARRANTY

M+S

S.Code	Size	LI SS	Sidewall	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Weight	UTQG	OE Fitment
						psi	lbs								
15															
1023440	235/75R15	XL 109T	OWL	6.5	6.0-8.0	50	2,271	28.8	9.2	7.4	11.5	722	33.3	660/A/B	
16															
1024100	215/70R16	100T	OWL	6.5	5.5-7.0	51	1,764	27.8	8.7	6.8	12.5	747	29.1	660/A/B	
1023441	225/70R16	103T	OWL	6.5	6.0-7.5	51	1,929	28.4	8.9	7.1	12.5	731	30.5	660/A/B	
1023442	225/75R16	XL 108T	OWL	6.0	6.0-7.5	50	2,183	29.2	8.7	7.1	12.5	710	32.8	660/A/B	
1023443	235/70R16	XL 109T	OWL	7.0	6.0-8.0	50	2,271	28.9	9.4	7.4	12.5	718	34.1	660/A/B	
1023444	235/75R16	XL 112T	OWL	6.5	6.0-8.0	50	2,649	29.8	9.1	7.4	12.5	698	35.4	660/A/B	
1023445	245/70R16	XL 111T	OWL	7.0	6.5-8.0	50	2,403	29.5	9.6	7.7	12.5	703	35.0	660/A/B	
1023446	245/75R16	111T	OWL	7.0	6.5-8.0	51	2,403	30.4	9.6	7.7	12.5	682	37.3	660/A/B	
1023447	255/65R16	109T	OWL	7.5	7.0-9.0	51	2,271	29.0	10.2	8.4	12.5	715	35.1	660/A/B	
1023448	255/70R16	111T	OWL	7.5	6.5-8.5	51	2,403	30.0	10.2	8.0	12.5	691	38.0	660/A/B	
1023449	265/70R16	112T	OWL	8.0	7.0-9.0	51	2,469	30.6	10.7	8.4	12.5	678	40.3	660/A/B	
1023450	265/75R16	116T	OWL	7.5	7.0-9.0	51	2,756	31.6	10.4	8.4	12.5	658	40.9	660/A/B	
17															
1023451	235/65R17	104T	OWL	7.0	6.5-8.5	51	1,984	29.0	9.6	7.8	12.5	716	34.2	660/A/B	
1023452	235/75R17	109T	OWL	6.5	6.0-8.0	51	2,271	30.8	9.2	7.4	12.5	674	35.6	660/A/B	
1023453	245/65R17	XL 111T	OWL	7.0	7.0-8.5	50	2,403	29.6	10.0	8.1	12.5	702	36.2	660/A/B	
1023454	245/70R17	110T	OWL	7.0	6.5-8.0	51	2,337	30.5	9.7	7.7	12.5	681	37.9	660/A/B	
1021539	245/75R17	112T	BSW	7.0	6.5-8.0	51	2,469	31.4	9.9	7.7	12.5	660	38.5	660/A/B	
1023455	255/65R17	110T	OWL	7.5	7.0-9.0	51	2,337	30.1	10.4	8.4	11.5	690	37.5	660/A/B	
1023456	255/70R17	112T	OWL	7.5	6.5-8.5	51	2,469	31.1	10.2	8.0	12.5	669	39.8	660/A/B	
1021538	255/75R17	115T	BSW	7.0	6.5-8.5	51	2,679	32.0	10.0	8.0	12.5	649	40.7	660/A/B	
1023457	265/65R17	112T	OWL	8.0	7.5-9.5	51	2,469	30.5	10.9	8.7	11.5	682	40.0	660/A/B	
1016678	265/70R17	115T	OWL	8.0	7.0-9.0	51	2,679	31.6	10.6	8.4	12.5	657	39.3	660/A/B	
18															
1024805	235/60R18	103T	BSW	7.0	6.5-8.5	51	1,929	29.1	9.9	7.8	12.5	715	33.4	660/A/B	
1021541	255/60R18	108T	BSW	7.5	7.0-9.0	51	2,205	30.0	11.2	8.4	12.5	693	37.8	660/A/B	
1021536	255/70R18	113T	BSW	7.5	6.5-8.5	51	2,535	32.0	10.7	8.0	12.5	648	41.1	660/A/B	
1021537	265/60R18	XL 114T	BSW	8.0	7.5-9.5	50	2,601	30.4	11.3	8.7	12.5	682	41.1	660/A/B	
1023458	265/65R18	114T	BSW	8.0	7.5-9.5	51	2,601	31.5	10.9	8.8	11.5	660	40.3	660/A/B	
1023459	265/70R18	116T	BSW	8.0	7.0-9.0	51	2,756	32.6	10.6	8.4	12.5	637	42.4	660/A/B	
1023460	275/65R18	116T	BSW	8.0	7.5-9.5	51	2,756	32.1	11.2	9.1	11.5	647	42.9	660/A/B	
20															
1025194	265/50R20	XL 111T	BSW	8.5	7.5-9.5	50	2,403	30.5	11.4	8.8	12.5	681	40.3	660/A/B	
1024188	275/55R20	113T	BSW	8.5	7.5-9.5	51	2,535	32.1	11.3	8.4	11.5	647	40.7	440/A/A FORD F-150 (18'21)	
1021535	275/60R20	115T	BSW	8.0	7.5-9.5	51	2,679	32.9	11.9	9.1	12.5	631	45.8	660/A/B	
1021540	305/50R20	XL 120T	BSW	9.5	8.5-11.0	50	3,086	32.0	13.2	10.1	13.0	650	47.8	660/A/B	
22															
1024103	285/45R22	110T	BSW	9.5	9.0-10.5	51	2,337	32.0	11.5	9.8	12.5	650	43.4	660/A/B	
1023462	305/45R22	XL 118T	BSW	10.0	9.5-11.5	50	2,910	32.7	12.1	10.4	12.5	635	46.7	660/A/B	

Technical data subject to change without prior notice.

XL : Extra Load BSW : Black Sidewall WSW : White Sidewall OWL : Outlined White Letters RWL : Raised White Letters Mileage, Road Hazard, and 30 Day Free Trial warranties apply only to replacement tires. Original Equipment tires are excluded.





Dynapro AT2



For aggressive all-terrain driving

The best on/off-road tire for 4x4 vehicles, the Dynapro AT2 employs a tough pattern design and block structure to overcome any road.

 Meets the severe snow service requirement of the U.S. Tire Manufacturer's Association (USTMA)



S.Code	Size	LI/SS	Sidewall	Ply Rating	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Weight
							psi	Lbs						
15														
2020845	30X9.50R15LT	104S	OWL	6 (C)	7.5	6.0-8.0	50	(S) 1,985	29.5	8.9	7.6	15.5	708	40.0
2020995	31X10.50R15LT	109S	OWL	6 (C)	8.5	7.0-9.0	50	(S) 2,270	30.5	9.9	8.4	15.5	686	44.2
2020847	33X12.50R15LT	108S	OWL	6 (C)	10.0	8.0-10.5	35	(S) 2,205	32.6	11.9	10.0	15.5	641	57.2
2021290	LT215/75R15	100/97S	OWL	6 (C)	6.0	5.5-7.0	50	(S) 1,765 (D) 1,610	27.6	8.5	6.8	14.5	758	34.4
2020844	LT235/75R15	104/101S	OWL	6 (C)	6.5	6.0-8.0	50	(S) 1,985 (D) 1,820	28.8	9.0	7.4	15.5	725	38.8
16														
2020848	LT215/85R16	115/112S	OWL	10 (E)	6.0	5.5-7.0	80	(S) 2,680 (D) 2,470	30.3	8.1	6.8	15.0	691	41.7
2020692	LT225/75R16	115/112S	BSW	10 (E)	6.0	6.0-7.5	80	(S) 2,680 (D) 2,470	29.2	9.0	7.1	15.0	716	42.3
2020849	LT235/85R16	120/116S	BSW	10 (E)	6.5	6.0-7.5	80	(S) 3,042 (D) 2,778	31.6	8.6	7.0	16.0	661	46.5
2020850	LT245/75R16	120/116S	OWL	10 (E)	7.0	6.5-8.0	80	(S) 3,042 (D) 2,778	30.4	9.5	7.7	15.5	688	45.5
2020851	LT265/70R16	117/114S	OWL	8 (D)	8.0	7.0-9.0	65	(S) 2,835 (D) 2,600	30.6	10.5	8.4	15.5	683	47.4
2020690	LT265/75R16	123/120S	BSW	10 (E)	7.5	7.0-9.0	80	(S) 3,415 (D) 3,085	31.7	10.3	8.3	15.5	660	50.9
2020871	LT285/75R16	126/123S	OWL	10 (E)	8.0	7.5-9.5	80	(S) 3,750 (D) 3,415	32.8	10.7	9.0	15.5	637	60.6
2020855	LT305/70R16	124/121S	OWL	10 (E)	9.0	8.0-10.0	65	(S) 3,525 (D) 3,195	32.8	11.9	9.6	15.5	637	62.4
2020856	LT315/75R16	121/118S	OWL	8 (D)	8.5	8.0-10.5	50	(S) 3,195 (D) 2,910	34.5	11.6	9.9	15.5	605	67.5
17														
2021066	35X12.50R17LT	121S	OWL	10 (E)	10.0	8.0-10.5	65	(S) 3,195	34.5	12.3	10.0	15.5	606	68.6
2020693	LT225/75R17	116/113S	BSW	10 (E)	6.0	6.0-7.5	80	(S) 2,755 (D) 2,535	30.2	8.8	7.1	15.0	691	43.6
2020691	LT235/80R17	120/117S	BSW	10 (E)	6.5	6.0-8.0	80	(S) 3,085 (D) 2,835	31.7	9.1	7.4	15.5	659	48.2
2020852	LT245/70R17	119/116S	OWL	10 (E)	7.0	6.5-8.0	80	(S) 3,000 (D) 2,755	30.5	9.6	7.7	15.5	685	46.1
2020853	LT245/75R17	121/118S	OWL	10 (E)	7.0	6.5-8.0	80	(S) 3,195 (D) 2,910	31.4	9.5	7.7	15.0	665	46.7
2020188	LT265/70R17	121/118S	OWL	10 (E)	8.0	7.0-9.0	80	(S) 3,195 (D) 2,910	31.6	10.5	8.3	15.0	661	48.8
2020857	LT275/70R17	121/118S	OWL	10 (E)	8.0	7.0-9.0	80	(S) 3,195 (D) 2,910	32.1	10.7	8.7	15.0	650	58.2
2020858	LT285/70R17	121/118S	OWL	10 (E)	8.5	7.5-9.5	80	(S) 3,195 (D) 2,910	32.7	11.2	9.0	15.5	639	60.2
2020859	LT295/70R17	121/118S	BSW	10 (E)	8.5	7.5-10.0	80	(S) 3,195 (D) 2,910	33.2	11.6	9.3	15.5	629	62.3
2020860	LT315/70R17	121/118S	OWL	10 (E)	9.5	8.0-10.5	65	(S) 3,195 (D) 2,910	34.4	12.3	9.9	15.5	608	66.9
18														
2021068	35X12.50R18LT	123S	BSW	10 (E)	10.0	8.5-11.0	65	(S) 3,415	34.5	12.2	10.0	15.0	605	72.7
2020854	LT265/70R18	124/121S	BSW	10 (E)	8.0	7.0-9.0	80	(S) 3,525 (D) 3,195	32.6	10.5	8.4	15.0	641	50.9
2020861	LT275/65R18	123/120S	BSW	10 (E)	8.0	8.0-9.5	80	(S) 3,415 (D) 3,085	32.0	11.0	9.1	15.0	652	63.7
2020862	LT275/70R18	125/122S	BSW	10 (E)	8.0	7.0-9.0	80	(S) 3,640 (D) 3,305	33.1	10.8	8.7	15.0	631	63.0
2020863	LT285/65R18	125/122S	BSW	10 (E)	8.5	8.5-10.0	80	(S) 3,640 (D) 3,195	32.5	11.5	9.4	14.5	643	64.9
2021067	LT305/65R18	124/121S	BSW	10 (E)	9.0	9.0-11.0	65	(S) 3,525 (D) 3,195	33.5	11.9	9.6	15.0	623	68.4
2020864	LT325/60R18	124/121S	BSW	10 (E)	9.5	9.5-11.5	65	(S) 3,525 (D) 3,195	33.3	13.2	10.7	14.5	628	70.6
2020865	LT325/65R18	127/124S	BSW	10 (E)	9.5	9.5-11.5	65	(S) 3,860 (D) 3,525	34.6	12.9	10.7	14.5	605	75.3
20														
2021074	35X12.50R20LT	121S	BSW	10 (E)	10.0	8.5-11.0	65	(S) 3,195	34.5	12.5	10.5	15.5	606	76.5
2021069	LT265/60R20	121/118S	BSW	10 (E)	8.0	8.0-9.5	80	(S) 3,195 (D) 2,910	32.4	11.0	8.3	14.5	645	54.6
2021070	LT275/55R20	115/112S	BSW	8 (D)	8.5	8.0-9.5	65	(S) 2,680 (D) 2,470	31.9	11.5	9.1	14.5	656	56.8
2021071	LT275/60R20	119/116S	BSW	8 (D)	8.0	8.0-9.5	65	(S) 3,000 (D) 2,755	32.9	11.1	9.1	14.5	635	58.6
2020866	LT275/65R20	126/123S	BSW	10 (E)	8.0	8.0-9.5	80	(S) 3,750 (D) 3,415	34.0	11.2	9.1	14.5	614	66.7
2020867	LT285/55R20	122/119S	BSW	10 (E)	9.0	8.5-10.0	80	(S) 3,305 (D) 3,000	32.4	11.1	9.4	16.0	646	63.4
2021072	LT285/65R20	127/124S	BSW	10 (E)	8.5	8.5-10.0	80	(S) 3,860 (D) 3,525	34.6	11.5	9.4	14.5	605	68.3
2021073	LT295/60R20	126/123S	BSW	10 (E)	8.5	8.5-10.5	80	(S) 3,750 (D) 3,415	33.9	12.1	9.3	15.0	617	71.1
2020868	LT305/55R20	121/118S	BSW	10 (E)	9.5	9.0-11.0	65	(S) 3,195 (D) 2,910	33.2	12.3	10.1	16.0	630	69.3
2020869	LT325/60R20	126/123S	BSW	10 (E)	9.5	9.5-11.5	65	(S) 3,750 (D) 3,415	35.3	12.9	10.8	15.5	592	76.0
22														
2020870	LT325/50R22	122S	BSW	10 (E)	10.0	9.5-11.5	65	(S) 3,305	34.8	13.3	10.8	16.0	600	78.4

Technical data subject to change without prior notice.
 XL : Extra Load BSW : Black Sidewall WSW : White Sidewall OWL : Outlined White Letters RWL : Raised White Letters