

Long Haul - Steer

Endurance® LHS®

Goodyear's Best Long Haul and Super-Regional Steer Tire for High Miles to Removal

- Optimized wear-resistant tread compound
- Dual-layer tread
- Premium rigid casing construction
- Advanced sidewall compound
- Pressure distribution groove



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	113	51	8.25	11.0	279	41.5	1,054	19.4	493	501	311	18	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	52	8.25	11.0	279	41.5	1,054	19.3	490	501	311	18	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	122	55	8.25	11.1	282	43.4	1,102	20.3	516	479	298	18	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	123	56	8.25	11.2	284	43.5	1,105	20.4	518	478	297	18	12.5	318	75	
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.0	279	41.5	1,054	19.5	495	501	311	18	12.5	318	75	
285/75R24.5	H	6,780	3,075	120	830	6,175	2,800	120	830	114	52	8.25	11.2	284	41.6	1,057	19.5	495	499	310	18	12.5	318	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75	
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	111	50	8.25	11.3	287	40.4	1,026	18.8	478	514	319	18	12.9	328	75	