

Regional/Urban - Steer/All Position

Endurance® RSA®

Goodyear's Best Regional and Urban All-Position Tire for Long Miles to Removal

- Innovative tread compound
- Special tread block geometry
- Premium rigid casing construction
- Wide solid shoulder tread design
- IntelliMax rib technology



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	109	50	7.50	10.1	257	40.4	1,026	19.0	483	514	319	21	11.4	290	75	
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	122	55	8.25	10.8	274	41.9	1,064	19.6	498	496	308	22	12.5	318	75	
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	123	56	8.25	10.8	274	41.9	1,064	19.6	498	496	308	22	12.5	318	75	
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	131	59	8.25	10.9	277	43.9	1,115	20.6	523	473	294	22	12.5	318	75	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	131	60	8.25	10.9	277	43.9	1,115	20.6	523	473	294	22	12.5	318	75	
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	141	64	9.00	11.6	295	43.1	1,095	20.2	513	482	300	22	13.5	343	75	
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	87	39	7.50	9.7	246	37.4	950	17.6	447	555	345	19	11.0	279	75	
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	93	42	7.50	10.0	254	36.7	932	17.3	439	566	352	18	11.3	287	81	
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	101	46	7.50	10.1	257	38.9	988	18.3	465	534	332	20	11.6	295	75	
275/70R22.5	J	6,940	3,150	130	900	6,395	2,900	130	900	105	48	7.50	10.5	267	38.0	965	17.7	450	547	340	19	11.9	302	75	
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	53	8.25	11.3	287	40.6	1,031	19.0	483	512	318	22	12.9	328	75	