

# Regional/Urban - Drive

## G182 RSD®

Goodyear's Best Regional Drive Tire for Long Miles to Removal

- Innovative tread compound
- Deep 28/32" open lug tread design
- Enhanced casing with steel belt package
- Mirrored, non-directional tread design
- Tie-Bar Shoulder And Bladed Tread Pattern



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm	
<b>TUBELESS TIRES ON 15° DROP CENTER RIMS</b>																								
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	123	56	8.25	10.8	274	42.1	1,069	19.6	498	496	308	28	12.5	318	75
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	125	57	8.25	10.8	274	42.1	1,069	19.6	498	496	308	28	12.5	318	75
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	139	63	8.25	11.0	279	44.1	1,120	20.8	528	473	294	28	12.5	318	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	141	64	8.25	11.0	279	44.1	1,120	20.8	528	473	294	28	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	297	43.4	1,102	20.4	518	481	299	28	13.5	343	75
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	118	54	8.25	11.3	287	40.8	1,036	19.0	483	512	318	28	12.9	328	75