HCS

Severe Service All-Position







PRODUCT DATA





	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		RF	REVS		RE	MAX. LOAD @ INFLATION	
TIRE SIZE																PER UNIT		WEIGHT		SINGLE	DUAL
					IN	ММ	IN	ММ	IN	ММ	IN	ММ	niin(3)	IN	ММ	MI	KM	LB	KG	LBS, PSI (KG, KPa)	LBS, PSI (KG, KPa)
445/65R22.5*	L	05350330000	27	68	20.9	532	45.5	1156	17.7	449	19.0	482	13.00, 14.00	N/A	N/A	462	287	207	94	12800, 130 (5800, 900)	N/A
325/95R24	J	05160330000	40	50	22.4	568	49.3	1252	12.8	325	13.1	332	8.50, 9.00	14.2	360	430	267	204	92	9370, 120 (4250, 830)	8540, 120 (3875, 830)
325/95R24 (NHS)	J	05160340000	40	50	22.4	568	49.3	1252	12.8	325	13.1	332	8.50, 9.00	14.2	360	430	267	204	92	9370, 120 (4250, 830)	8540, 120 (3875, 830)
						TUE	ELESS	TIRES	ON 15	DEGRE	E DRO	P CENT	ER RIMS								

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. NHS - Not for Highway Use Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



High operational safety, long lasting service and outstanding resistance to damage through compounds with extreme resistance to cuts and tears.



Outstanding traction, even in harshest terrain, thanks to tread pattern structure and geometry.



Most durable casing design for maximum service life in demanding off-road use, also involving heavy-duty vehicles.

Applications: All-Position service for on/off road, mining and heavy mix axles.