

REGIONAL TO URBAN ALL-POSITION TIRE

The M122 is a versatile all-position tire designed for moderate regional and urban applications. Recommended for steer but suitable for all positions, the durable M122 covers a wide segment of the market. All-steel, four-belt construction provides even tread wear plus extended tire and casing life. Other life-extending features include a solid outer rib and special cap-and-base tread compounding. This base, regional to urban pickup and delivery tire combines product performance, application versatility, and a competitive acquisition point for a lower cost per mile, making it a leading value alternative tire.

M122

APPLICATION	RECOMMENDED	SUITABLE
LONG HAUL	TRAILER	STEER, DRIVE
REGIONAL	STEER, TRAILER	DRIVE
URBAN	STEER, TRAILER	DRIVE

LONG TREAD LIFE

- DSOC II™ technology optimizes footprint design for even wear and long life.
- Wide five-rib pattern with a solid outer rib and 17/32" tread depth combine for long, even wear.

GREAT PERFORMANCE AND SAFETY

- Wide five-rib pattern with a solid outer rib improves stability and handling performance.

DEPENDABLE RETREADABILITY AND CASING DURABILITY

- Four-steel-belt construction braces the tread area, improving durability.
- Stone-ejector grooves minimize stone retention to maintain casing integrity.
- High-elongation top belt protects casing integrity.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (17/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED RADIUS (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	11R22.5	G/14	548020	75	7.5-(8.25)	115	17	41.3	11.1	19.1	12.1	6175	5840	105	105	503
	255/70R22.5	H/16	548150	75	(7.50) -8.25	88	17	36.6	9.9	16.8	10.8	5510	5070	120	120	567
	295/75R22.5	G/14	548000	75	8.25-(9.00)	106	17	40.0	11.1	18.6	12.1	6175	5675	110	110	518
24.5	11R24.5	G/14	548010	75	7.5-(8.25)	121	17	43.3	11.1	20.1	12.1	6610	6005	105	105	480
	285/75R24.5	G/14	548030	75	8.25	109	17	41.1	10.8	19.1	11.7	6175	5675	110	110	505

Bold designates measuring rim width.
*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.