

LOW-PLATFORM TRAILER TIRE

The M1430 is the ideal 17.5" tire for low-platform and high-cube trailers in regional, urban, and long haul applications. The high miles per 32nd, with minimized irregular wear, results in excellent removal miles. This, combined with a competitive acquisition point, makes the M1430 a leading value alternative low-platform trailer tire.

APPLICATION	RECOMMENDED	SUITABLE
LONG HAUL	TRAILER	-
REGIONAL	TRAILER	-
URBAN	TRAILER	-

MAXIMUM REMOVAL MILES

- DSOC II™ technology optimizes footprint design for even wear and long life.
- Five-rib, four-groove pattern with a solid outer rib and tread depth combine for long, even wear.

HIGH-LOAD CARRYING CAPACITY

- Wide-belt construction braces the tread area for increased load-carrying capacity.
- Enhanced bead construction stabilizes the casing for heavy loads.

EXCEPTIONAL CASING DURABILITY

- Stone-ejector grooves minimize stone retention to maintain casing integrity.
- High-elongation top belt protects casing integrity.



M1430

WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
17.5	215/75R17.5	H/16	520500	62	(6.0)-6.75	60	15	30.5	8.3	14.2	9.1	4805	4540	125	125	681
	235/75R17.5	J/18	520540	62	(6.75)-7.50	65	15	31.6	9.2	14.3	10.0	6005	5675	125	125	657
	245/70R17.5	J/18	520530	62	(6.75)-7.50	69	16	31.5	9.5	14.6	10.3	6005	5675	125	125	660