

REGIONAL TO URBAN STEER TIRE

The M153 is an extra-deep 26/32" regional and urban heavy-duty steer tire optimized for extremely high-scrub applications, where tread wear is the primary reason for tire removal. State-of-the-art design and compounding deliver superior wear performance and excellent durability with a 10,000-lb. load-carrying capacity. These benefits combine with a competitive acquisition point to make the M153 an excellent refuse tire and a leading value alternative tire for all tough operations.

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	STEER	DRIVE, TRAILER
URBAN	STEER	DRIVE, TRAILER

MAXIMUM REMOVAL MILES

- E-balance provides optimum footprint wear to increase mileage performance.
- Deep 26/32" tread depth delivers longer wear life under high-scrub conditions.
- Extremely wide tread pattern distributes heavy loads evenly to improve mileage.

EXCELLENT PERFORMANCE AND SAFETY

- Z-shaped siping in tread increases traction in wet conditions.

EXCEPTIONAL RETREADABILITY AND CASING DURABILITY

- Unique buttress protector reduces cutting and curb damage to the sidewall.
- Wide steel-belt construction braces the tread area, improving durability, while high-elongation top belt protects casing integrity.
- High-tensile, open-cord construction keeps moisture and oxygen from entering the cord bundle to combat corrosion.
- Stone-ejector grooves minimize stone retention to maintain casing integrity.



M153

WHEEL DIA.	TIRE SIZE	LOAD RANGE/PLY RATING	PRODUCT CODE	MAX. SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED WIDTH (IN.)	MAX. LOAD (LBS.) SINGLE	MAX. LOAD (LBS.) DUAL	MAX. PRESSURE (PSI) SINGLE	MAX. PRESSURE (PSI) DUAL	REVS PER MILE
22.5	315/80R22.5	L/20	500040	68	(9.00)-9.75	168	26	43.0	12.3	19.2	13.4	10000	9090	130	130	484