

REGIONAL TO URBAN DEEP ALL-POSITION TIRE

The M154 is a deep all-position tire designed for regional to urban service in the highest-scrub environments, where tread wear is the primary reason for tire removal. Users can typically expect a return on their investment in less than a year with this SmartWay-verified tire. Excellent, even wear in miles per 32nd and a deep tread up to 22/32" deliver maximum removal mileage, even in the drive position. Excellent fuel efficiency and high mileage make the M154 the leading value alternative tire for regional to urban high-scrub applications.

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	STEER	DRIVE, TRAILER
URBAN	STEER	DRIVE, TRAILER



M154

MAXIMUM REMOVAL MILES

- E-balance provides optimum footprint wear to increase mileage performance.
- Wide five-rib pattern with a solid outer rib and optimized tread depth combine for long, even wear.
- Special cap-and-base tread compound extends tire life by reducing heat buildup and resisting wear.

MAXIMUM FUEL EFFICIENCY

- Low-rolling-resistance construction minimizes fuel consumption and qualifies it as a SmartWay-verified steer tire.

EXCELLENT PERFORMANCE AND SAFETY

- Computer-optimized tread design, with four straight grooves, deep sipes, and multi-pitch grooves, provides enhanced wet and dry traction while also reducing road noise.

MAXIMUM RETREADABILITY AND CASING DURABILITY

- E-balance profile minimizes growth of the tread profile and maintains uniform and flatter tread radius for the entire life of the casing.
- High-elongation top belt protects casing integrity.
- High-tensile, open-cord construction keeps moisture and oxygen from entering the cord bundle to combat corrosion.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)	STATIC LOAD WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
19.5	225/70R19.5	G/14	548860	87	(6.00) -6.75	73	17	32.1	8.3	14.7	9.1	3970	3750	110	110	647
	245/70R19.5	H/16	548840	87	6.75- (7.50)	81	18	33.3	9.6	15.1	10.5	4940	4675	120	120	624
22.5	11R22.5	G/14	548330	75	7.50- (8.25)	122	22	41.5	11.1	18.7	12.1	6175	5840	105	105	500
	11R22.5	H/16	548310	75	7.50- (8.25)	123	22	41.5	11.1	18.7	12.1	6610	6005	120	120	500
	245/75R22.5	G/14	548770	75	6.75- (7.50)	89	19	37.0	9.5	17.2	10.2	4675	4300	110	110	561
	265/75R22.5	G/14	548760	75	(7.50) -8.25	99	19	38.4	10.0	17.9	10.9	5205	4805	110	110	540
	295/75R22.5	G/14	548250	75	(8.25) -9.00	118	22	40.4	11.1	18.2	12.1	6175	5675	110	110	514
24.5	295/75R22.5	H/16	548230	75	(8.25) -9.00	119	22	40.4	11.1	18.2	12.1	6610	6005	120	120	514
	11R24.5	G/14	548300	75	7.50- (8.25)	131	22	43.5	11.1	19.7	12.1	6610	6005	105	105	477
	11R24.5	H/16	548290	75	7.50- (8.25)	132	22	43.5	11.1	19.7	12.1	7160	6610	120	120	477
	285/75R24.5	G/14	548260	75	8.25	120	22	41.5	10.8	18.9	11.8	6175	5675	110	110	501

Bold designates measuring rim width.
*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.