

REGIONAL AND URBAN STEER TIRE

The M170 steer tire is designed for demanding regional and urban operations, where tread wear is the primary reason for tire removal. Excellent even wear in miles per 32nd with a deep 19/32" tread depth results in maximum removal mileage. This, combined with excellent fuel efficiency and a very competitive acquisition point, results in a lower cost per mile, making the M170 a leading value alternative tire in regional high-scrub applications that typically delivers a return on investment within a year.

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	STEER	DRIVE, TRAILER
URBAN	STEER	DRIVE, TRAILER



M170

EXCELLENT REMOVAL MILES

- E-balance provides optimum footprint wear to increase mileage performance.
- Wide five-rib pattern with a solid outer rib and optimized tread depth combine for long, even wear.

HIGH FUEL EFFICIENCY

- Low-rolling-resistance construction minimizes fuel consumption.

EXCELLENT RETREADABILITY AND CASING DURABILITY

- E-balance profile minimizes growth of the tread profile, and maintains uniform and flatter tread radius for the entire life of the casing.
- High-elongation top belt protects casing integrity.
- V-shaped groove design ejects packed stones at low speeds to prevent stone drilling.



WHEEL DIA.	TIRE SIZE	LOAD RANGE / PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	10R22.5	G/14	548350	75	6.75-(7.50)-8.25	99	19	40.0	10.0	18.1	10.9	5675	5355	115	115	519
	11R22.5	H/16	546000	75	7.50-(8.25)	116	19	41.3	11.1	16.1	12.1	6610	6005	120	120	503
	12R22.5	H/16	546310	75	8.25-(9.00)	132	19	42.4	12.4	19.7	13.4	7390	6780	120	120	490
	295/75R22.5	H/16	546020	75	(8.25)-9.00	119	19	40.2	11.1	18.1	12.1	7160	6610	125	125	517
	9R22.5	F/12	546030	75	6.00-(6.75)-7.50	86	17	38.2	9.1	17.8	9.9	4540	4300	105	105	544
24.5	11R24.5	H/16	546010	75	7.50-(8.25)	133	19	43.4	11.1	19.6	12.1	7160	6610	120	120	479

*F" = 12-ply rating, "G" = 14-ply rating, "H" = 16-ply rating. Bold designates measuring rim width.
 *Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.
 ©2015 Toyo Tire U.S.A. Corp. #180723 Published March 2015

TOYO TIRES®

THE LEADING VALUE ALTERNATIVE TIRES.

Toyo commercial tires combine top-tier product performance, application versatility, and a competitive acquisition point for a lower cost per mile, making it a leading value alternative brand. Peace of mind and maximum profitability – standard with every purchase.

THE LONGEST WARRANTY

We believe so strongly in our quality that we offer a 66-month limited warranty on our entire truck tire line. It includes casing allowances for two retreads and a retread rubber allowance for the first cap. Our warranty is yet another reason why Toyo Tires is the right choice. Contact your local Toyo Tires Regional Sales Representative for additional details.

RELIABLE



TOYOTIRES.COM/TBR