

## ON/OFF-ROAD TIRE

The M320 WB is an even-wearing, wide base on/off-road tire built for multiple applications in the most demanding high-traction, high-torque environments. Designed for logging, mining, concrete mixers, and refuse trucks, this cut- and chip-resistant tire delivers extended tread life, superb traction, and exceptional durability. These benefits, combined with a competitive acquisition point, make the M320 the leading value alternative wide base tire in the on/off-road segment.

APPLICATION	RECOMMENDED	SUITABLE
URBAN	STEER	DRIVE, TRAILER
ON/OFF-ROAD	STEER	DRIVE

M320 WB

### MAXIMUM REMOVAL MILES

- Tough tread compound resists cuts and chips to extend tire life.
- DSOC II™ technology optimizes footprint design for even wear and long life.

### EXCELLENT PERFORMANCE AND SAFETY

- Deep tread provides traction in tough on/off-road conditions.
- High natural rubber content delivers unmatched cut and chip resistance.

### ENHANCED RETREADABILITY AND CASING DURABILITY

- High-elongation top belt protects casing integrity.
- Stone-ejector grooves minimize stone retention to maintain casing integrity.
- Four-steel-belt construction contributes to casing durability.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	385/65R22.5	J/18	549070	68	<b>(11.75)</b> -12.25	169	22	42.6	14.8	19.8	15.6	9370	-	120	-	487
	425/65R22.5	L/20	549090	68	11.75- <b>(12.25)</b> -13.00	195	23	44.9	16.3	20.9	17.3	11400	-	120	-	462

Bold designates measuring rim width.

\*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.