

REGIONAL AND URBAN DRIVE TIRE

The M610 is a deep, open-shoulder drive tire that delivers high traction, high torque, and cut and chip resistance plus high mileage. The tire comes with a 28/32" tread depth, which adds to its long life. These benefits, plus a competitive acquisition point, make the M610 a leading value alternative tire popular with fleets.

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	DRIVE	-
URBAN	DRIVE	-

EXCELLENT TRACTION

- Deep 28/32" open-shoulder tread provides traction in both wet and dry conditions.
- High-traction, high-torque tread design prevents block tearing.

MAXIMUM REMOVAL MILES

- DSOC II™ technology optimizes footprint design for even wear and long life.
- Deep 28/32" tread depth delivers longer life.
- Tie bars in shoulder bridge reduce tread block movement.

EXCEPTIONAL RETREADABILITY AND CASING DURABILITY

- Four-steel-belt construction braces the tread area, improving durability.
- V-shaped groove design ejects packed stone at low speeds to prevent stone drilling.
- High-elongation top belt protects casing integrity.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	11R22.5	G/14	556350	75	7.50-(8.25)	125	28	42.0	11.1	18.8	12.1	6175	5840	105	105	495
	11R22.5	H/16	556330	75	7.50-(8.25)	124	28	42.0	11.1	18.8	12.1	6610	6005	120	120	495
	295/75R22.5	G/14	556380	75	(8.25)-9.00	120	28	40.7	11.1	18.4	12.1	6175	5675	110	110	510
24.5	11R24.5	G/14	556460	75	8.25	138	28	44.0	11.1	20.4	12.1	6610	6005	105	105	471
	11R24.5	H/16	556470	75	8.25	138	28	44.0	11.1	20.4	12.1	7160	6610	120	120	471
	285/75R24.5	G/14	556500	75	8.25	130	28	42.0	11.1	19.5	12.1	6175	5675	110	110	494