

REGIONAL AND URBAN DRIVE TIRE

The M650 is a deep, open-shoulder drive tire designed for high torque applications. It delivers traction and high mileage while providing great cut and chip resistance. The tire comes with a 28/32" tread depth, which adds to its long life. All of these benefits, plus a low-rolling-resistance tread and competitive acquisition point, make the SmartWay-verified M650 a leading value alternative tire popular with fleets.

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	DRIVE	-
URBAN	DRIVE	-



MAXIMUM FUEL EFFICIENCY

- Low-rolling-resistance tread compound minimizes fuel consumption and qualifies it as a SmartWay-verified drive tire.

EXCELLENT TRACTION

- Deep 28/32", open-shoulder tread provides traction in both wet and dry conditions.
- High-traction, high-torque tread design prevents block tearing.

MAXIMUM REMOVAL MILES

- E-balance provides optimum footprint wear to increase mileage performance.
- Deep 28/32" tread depth delivers longer life.
- Tie bars in shoulder bridge reduce tread block movement.

EXCEPTIONAL RETREADABILITY AND CASING DURABILITY

- E-balance profile minimizes growth of the tread profile and maintains uniform and flatter tread radius for the entire life of the casing.
- V-shaped groove design ejects packed stones at low speeds to prevent stone drilling.
- High-elongation top belt protects casing integrity.



M650

WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)	STATIC LOADED RADIUS (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	11R22.5	G/14	558820	75	7.50-(8.25)	125	28	42.0	11.1	18.8	12.1	6175	5840	105	105	495
	11R22.5	H/16	558830	75	7.50-(8.25)	125	28	42.0	11.1	18.8	12.1	6610	6005	120	120	495
	295/75R22.5	G/14	558800	75	(8.25)-9.00	120	28	40.7	11.1	18.4	12.1	6175	5675	110	110	510