

M920™ (22.5-24.5)

LONG HAUL, REGIONAL, AND URBAN DRIVE TIRE

The M920 drive tire delivers superb all-season traction and high mileage for long haul, regional and urban operations. This unique tire features a wider tread width for even load distribution and improved stability. Deep tread depth ensures maximum mileage in a variety of applications. Computer-optimized design, all-season traction, and high mileage combine with a competitive acquisition point to make the M920 the leading value alternative for regional and local vehicles.

APPLICATION	RECOMMENDED	SUITABLE
LONG HAUL	DRIVE	-
REGIONAL	DRIVE	-
URBAN	DRIVE	-



Three-Peak Mountain Snowflake qualified for severe snow conditions.

M920 (22.5-24.5)

MAXIMUM REMOVAL MILES

- Extra-deep tread depth delivers maximum miles.
- E-balance provides optimum footprint wear to increase mileage performance.
- Wider tread width for even load distribution, improved stability, and excellent profile retention.
- Super-thin sipes decrease block movement under driving and braking conditions to deliver more even wear.

SUPERIOR ALL-SEASON PERFORMANCE

- Optimized staggered shoulder blocks provide exceptional all-season traction.
- Cross-sipe arrangement maintains block stiffness to provide traction throughout the life of the tire.

EXCELLENT CASING DURABILITY

- E-balance profile minimizes growth of the tread profile and maintains uniform and flatter tread radius for the entire life of the casing.
- Stone ejectors in all major grooves prevent casing damage.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	11R22.5	G/14	540100	75	7.50-(8.25)	128	27	41.9	11.1	19.5	12.1	6175	5840	105	105	495
	11R22.5	H/16	540090	75	7.50-(8.25)	128	27	41.9	11.1	19.5	12.1	6610	6005	120	120	495
	295/75R22.5	G/14	540170	75	(8.25) -9.00	127	27	40.7	11.1	18.9	12.1	6175	5675	110	110	510
	315/80R22.5	L/20	540190	75	(9.00) -9.75	174	29	43.1	12.3	20.1	13.4	9090	8270	130	130	481
24.5	11R24.5	H/16	540140	75	7.50-(8.25)	139	27	43.9	11.1	20.4	12.1	7160	6610	120	120	473
	285/75R24.5	G/14	540160	75	8.25	132	27	41.9	10.8	19.5	11.8	6175	5675	110	110	496

Bold designates measuring rim width.
*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.

For the latest tire information please visit toyotires.com/commercial

