

Long Haul - Steer

Marathon® LHS®

Long Haul Steer Tire for High Miles to Removal

- Dependable tread compounds
- Five-rib construction
- Enhanced casing
- Lateral grooves and rib edge sipes



SmartWay® Verified



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	114	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75		
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	114	52	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	122	55	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	123	56	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	113	51	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75		
295/75R22.5	H	7,160	3,250	123	850	6,610	3,000	123	850	111	50	8.25	11.2	284	40.3	1,024	18.8	478	515	320	18	12.9	328	75		