

Regional/Urban - Drive

Marathon® RSD®

Regional Drive Tire for Long Miles to Removal

- Dependable tread compounds
- Solid shoulder tread design with 28/32" depth
- Enhanced casing
- Stone protectors



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	121	55	8.25	11.0	279	42.2	1,072	19.8	503	495	308	28	12.5	318	75		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	138	63	0.00	0.0	0	0.0	0	20.6	523	472	293	28	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	126	57	0.00	0.0	0	0.0	0	19.9	505	493	306	28	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	54	0.00	0.0	0	0.0	0	19.2	488	509	316	28	12.9	328	75		