

Regional/Urban - Steer/All Position

Marathon® RSS®

Regional and Urban All-Position Tire for Long Miles to Removal

- Dependable high scrub compounds
- Solid shoulder tread design
- Enhanced casing
- Computer-optimized tread design



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	88	40	8.25	11.2	284	41.5	1,054	19.5	495	501	311	18	12.5	318	75		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	104	47	8.25	11.3	286	43.6	1,107	20.5	521	476	296	18	12.5	318	75		
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	86	39	7.50	10.0	254	36.6	930	17.1	434	563	350	15	11.3	287	81		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	110	50	8.25	10.9	277	41.6	1,057	19.4	493	499	310	17	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	111	50	8.25	11.2	284	40.3	1,024	18.9	480	515	320	18	12.9	328	75		