

OPEN COUNTRY H/T II*

HIGHWAY ALL-SEASON TIRE

The all-new Open Country H/T II builds on the quality and reputation of the Open Country H/T. Advanced technology and design provide improved wet braking performance and handling, longer tread life, and more consistent performance throughout the life of the tire. Light truck and SUV owners will appreciate the dual sidewall design – sporty on one side, classic on the other – that lets them choose the look that complements their vehicle. This premium all-season tire comes with up to a 70,000-mile treadwear warranty and is backed by the Toyo Tires 500 Mile Trial Offer.

MILEAGE WARRANTY*

P/Euro-Metric Sizes: 70,000 miles
LT Sizes: 50,000 miles

UTQG

P/Euro-Metric Sizes: S/T-Rated: 740
A B and H/V-Rated: 740 A A



WEAR-RESISTANT TREAD COMPOUND

- Extends tread life and durability.

ADAPTIVE CIRCUMFERENTIAL GROOVE

- Helps maintain good wet performance throughout the life of the tire.

EXPANDING SHOULDER GROOVE

- Helps maintain good wet performance throughout the life of the tire.

MULTI-WAVE SIPES

- Minimizes irregular wear for a smooth, quiet ride.
- Improves braking on wet and dry roads.
- Improves light snow traction

FOUR WIDE CIRCUMFERENTIAL GROOVES

- Evacuates water to improve wet traction.

DUAL SIDEWALL DESIGN

- Offers two distinct looks for customizing; one sporty and one classic.

POPULAR FITMENTS

Cadillac/Chevrolet/GMC Trucks & SUVs
Dodge SUVs
Ford Trucks & SUVs
Nissan/Infiniti Trucks & SUVs
Ram Trucks
Toyota/Lexus Trucks & SUVs



WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
15	235/75R15	109T	XL	OWL	364720	6.0-(6.5)-8.0	32.8	11.8	28.9	9.3	2271	-	50	720
	215/70R16	100H	SL	BSW	364500	5.5-(6.5)-7.0	27.1	11.5	27.9	8.7	1764	-	51	745
	LT215/85R16	115/112S	E	BSW	364290	5.5-(6.0)-7.0	38.3	14.2	30.4	8.5	2680	2470	80	683
	LT225/75R16	115/112S	E	BSW	364250	(6.0)-7.0	38.1	14.1	29.3	8.8	2680	2470	80	709
16	235/70R16	109T	XL	OWL	364530	6.0-(7.0)-8.0	31.3	11.7	29	9.4	2271	-	50	717
	LT235/85R16	120/116S	E	OWL	364280	6.0-(6.5)-7.5	44.3	14.5	31.7	9.3	3042	2780	80	655
	245/70R16	107T	SL	OWL	364690	6.5-(7.0)-8.0	32.8	11.8	29.5	9.8	2149	-	44	704
	LT245/75R16	120/116S	E	OWL	364240	6.5-(7.0)-8.0	42.1	14.4	30.5	9.8	3042	2778	80	682

*See toyotires.com for details.

LIGHT TRUCK / SUV / CUV

LT

SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
16	245/75R16	111T	SL	OWL	364700	6.5-(7.0)-8.0	33.1	12	30.5	9.8	2403	-	44	682
	255/70R16	111T	SL	OWL	364640	6.5-(7.5)-8.5	35.5	12	30.1	10.2	2403	-	44	691
	265/70R16	112T	SL	BSW	364520	7.0-(8.0)-9.0	38.1	12.1	30.6	10.7	2469	-	44	678
	265/70R16	112T	SL	OWL	364510	7.0-(8.0)-9.0	38.1	12.1	30.6	10.7	2469	-	44	678
	LT265/75R16	123/120S	E	OWL	364310	7.0-(7.5)-8.0	25	13.5	31.7	10.5	3415	3085	80	656
	265/75R16	116T	SL	OWL	364730	7.0-(7.5)-9.0	40.4	12.2	31.7	10.5	2756	-	44	656
	LT285/75R16	126/123S	E	OWL	364410	7.5-(8.0)-9.0	11.2	15.7	32.8	11.3	3750	3415	80	633
17	225/65R17	102H	SL	BSW	364450	6.0-(6.5)-8.0	31	11.5	28.5	9	1874	-	51	729
	235/65R17	104T	SL	BSW	364460	6.5-(7.0)-8.5	32.7	11.6	29.1	9.4	1984	-	44	715
	235/70R17	109T	XL	OWL	364710	6.0-(7.0)-8.0	33.5	11.7	30	9.4	2271	-	50	692
	235/75R17	109T	SL	OWL	364660	6.0-(6.5)-8.0	34.6	11.8	30.9	9.3	2271	-	44	673
	LT235/80R17	120/117S	E	BSW	364300	6.0-(6.5)-7.5	45.4	14.4	31.8	9.3	3085	2835	80	653
	245/65R17	107H	SL	BSW	364490	7.0-(7.0)-8.5	34	11.7	29.5	9.8	2149	-	51	704
	LT245/70R17	119/116S	E	OWL	364340	6.5-(7.0)-8.0	43.1	14.2	30.6	9.8	3000	2755	80	680
	245/70R17	110T	SL	OWL	364540	6.5-(7.0)-8.0	35.5	11.8	30.6	9.8	2337	-	44	680
	LT245/75R17	121/118S	E	BSW	364220	6.5-(7.0)-7.5	44.5	14.4	31.5	9.8	3195	2910	80	660
	LT245/75R17	121/118S	E	OWL	364230	6.5-(7.0)-7.5	44.5	14.4	31.5	9.8	3195	2910	80	660
	255/65R17	110T	SL	OWL	364630	7.0-(7.5)-9.0	36.2	11.8	30.1	10.2	2337	-	44	691
	255/70R17	112T	SL	OWL	364600	6.5-(7.5)-8.5	35.5	12	31.1	10.2	2469	-	44	668
	265/65R17	112T	SL	OWL	364550	7.5-(8.0)-9.5	38.1	12	30.6	10.7	2469	-	44	680
	LT265/70R17	121/118S	E	BSW	364270	7.0-(8.0)-8.5	49.1	14.5	31.7	10.7	3195	2910	80	656
	LT265/70R17	121/118S	E	OWL	364260	7.0-(8.0)-8.5	46.9	14.5	31.7	10.7	3195	2910	80	656
	265/70R17	115T	SL	BSW	364430	7.0-(8.0)-9.0	41.1	12.1	31.7	10.7	2679	-	44	656
265/70R17	115T	SL	OWL	364440	7.0-(8.0)-9.0	39.9	12.1	31.7	10.7	2679	-	44	656	
LT285/70R17	121/118S	E	OWL	364360	7.5-(8.5)-9.0	53.4	15.7	32.8	11.5	3195	2910	80	634	
18	LT255/65R18	120/117R	E	BSW	364420	7.0-(7.5)-9.0	47.6	14.2	31.1	10.2	3085	2835	80	669
	255/65R18	111T	SL	BSW	364570	7.0-(7.5)-9.0	37.8	11.8	31.1	10.2	2403	-	44	669
	255/70R18	113S	SL	BSW	364740	6.5-(7.5)-8.5	41.1	12	32.1	10.2	2535	-	44	647
	265/60R18	110T	SL	BSW	364560	7.5-(8.0)-9.5	39	11.8	30.5	10.7	2337	-	44	681
	265/65R18	114T	SL	BSW	364610	7.5-(8.0)-9.5	39.2	12	31.5	10.7	2601	-	44	659
	265/70R18	116T	SL	BSW	364620	7.0-(8.0)-9.0	43	12.1	32.6	10.7	2756	-	44	636
	LT275/65R18	123/120S	E	BSW	364320	7.5-(8.0)-9.0	52	14.5	32.1	11	3415	3085	80	647
	275/65R18	116T	SL	BSW	364470	7.5-(8.0)-9.5	42.7	12.1	32.1	11	2756	-	44	647
	LT275/70R18	125/122S	E	BSW	364330	7.0-(8.0)-8.5	52.8	14.6	33.2	11	3640	3305	80	626
	285/60R18	120V	XL	BSW	364750	8.0-(8.5)-10.0	43.3	11.5	31.5	11.5	3086	-	50	660
20	255/50R20	109H	XL	BSW	364670	7.0-(8.0)-9.0	37.5	10.8	30.1	10.4	2271	-	50	691
	255/55R20	110H	XL	BSW	364650	7.0-(8.0)-9.0	42.4	11	31	10.4	2337	-	50	670
	265/50R20	107T	SL	BSW	364580	7.5-(8.5)-9.5	38.9	11.6	30.5	10.9	2149	-	44	682
	LT265/60R20	121/118S	E	BSW	364370	7.5-(8.0)-9.5	53	14.2	32.5	10.7	3195	2910	80	639
	275/55R20	117H	XL	BSW	364480	7.5-(8.5)-9.5	42.7	11.2	31.9	11.2	2833	-	50	651
	LT275/60R20	123/120R	E	BSW	364350	7.5-(8.0)-9.5	54.7	14.4	33	11	3415	3085	80	630
	275/60R20	115T	SL	BSW	364680	7.5-(8.0)-9.5	43.8	12	33	11	2679	-	44	630
	LT275/65R20	126/123S	E	BSW	364390	7.5-(8.0)-9.5	56.6	14.5	34.1	11	3750	3415	80	609
	285/50R20	112V	SL	BSW	364760	8.0-(9.0)-10.0	44.5	11.2	31.3	11.7	2469	-	51	665
	LT285/60R20	125/122R	E	BSW	364380	8.0-(8.5)-10.0	59.2	15.7	33.5	11.5	3640	3305	80	621
LT285/65R20	127/124R	E	BSW	364400	8.0-(8.5)-10.0	60.3	15.7	34.6	11.5	3860	3525	80	601	
21	275/50R21	113V	XL	BSW	364780	7.5-(8.5)-9.5	40.3	11.1	31.9	11.2	2535	-	50	652
22	275/50R22	111H	SL	BSW	364770	7.5-(8.5)-9.5	45.3	11.1	32.9	11.2	2403	-	51	632
	285/45R22	114H	XL	BSW	364590	9.0-(9.5)-10.5	41.9	11.1	32.1	11.2	2601	-	50	647

LIGHT TRUCK / SUV / CUV

LT

Speed rated "S" = 112 mph, "T" = 118 mph, "H" = 130 mph. "SL" = Standard Load, "BSW" = Black Sidewall, "WWW" = White Sidewall. Bold designates measuring rim width. *Inflated dimensions.