

HIGH TURN-UP, 3-PLY
POLYESTER CONSTRUCTION

- Contributes to excellent durability, impact resistance, and handling.

OPEN COUNTRY M/T

LIGHT TRUCK / SUV / CUV

LT

AGGRESSIVE TREAD DESIGN
WITH HOOK-SHAPED BLOCKS

- Delivers excellent off-road traction while maintaining great on-road performance.

OPEN, SCALLOPED
SHOULDER BLOCKS

- Improves off-road traction.
- Enhances grip in muddy, sandy, or snowy off-road conditions.
- Ejects mud and snow through the open channels.

OVER-THE-SHOULDER TREAD

- Helps to provide traction in deep mud and snow.
- Delivers improved off-road handling in hard turns.

DEEP SIPING IN THE
TREAD BLOCKS

- Helps maintain grip on wet surfaces.



*See toyotires.com for details.

For the latest tire information, please visit toyotires.com. **TOYO TIRES®**

OPEN COUNTRY M/T®

LT

LIGHT TRUCK / SUV / SUV

	WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
15		31X10.50R15LT	109Q	C	BSW	360490	7.0-(8.5)-9.0	57	19.1	31.1	10.7	2270	-	50	667
		33X10.50R15LT	114P	C	BSW	360470	7.0-(8.5)-9.0	64	19.1	32.8	10.9	2600	-	50	632
		33x12.50R15LT	108P	C	BSW	360100	8.0-(10.0)-11.0	73	21.0	33.0	12.8	2205	-	35	628
		33X13.50R15LT	109Q	C	BSW	360290	8.5-(11.0)	76	21.0	33.1	13.9	2270	-	35	628
		35X13.50R15LT	114Q	C	BSW	361000	8.5-(11.0)	82	21.0	34.8	14.4	2600	-	35	596
		37X14.50R15LT	120Q	C	BSW	360260	10.0-(12.0)	103	21.0	36.7	15.6	3080	-	35	566
16		LT235/85R16	120/116P	E	BSW	360440	6.0-(6.5)-7.5	54	18.4	32.0	9.4	3042	2778	80	648
		LT245/75R16	120/116P	E	BSW	360450	6.5-(7.0)-8.0	52	18.4	30.7	9.9	3042	2778	80	674
		LT255/85R16 (33X10.00R16)	123/120P	E	BSW	360460	6.5-(7.0)-8.0	61	18.9	33.5	10.2	3415	3085	80	619
		LT265/75R16	123P	E	BSW	360320	7.0-(7.5)-8.0	61	18.9	31.8	10.8	3415	-	80	651
		LT285/75R16 (33X11.50R16)	126P	E	BSW	360280	7.5-(8.0)-9.0	67	19.1	33.0	11.6	3740	-	80	628
		LT305/70R16 (33.DX12.00R16)	124P	E	BSW	360110	8.0-(9.0)-9.5	70	20.0	33.0	12.2	3525	-	65	628
17		LT315/75R16 (35X12.50R16)	127Q	E	BSW	360230	8.0-(8.5)-10.0	81	21.0	34.9	12.9	3860	-	65	595
		LT385/70R16 (38X14.50R16)	130Q	D	BSW	360480	10.0-(11.0)-12.0	102	21.0	37.7	15.6	4190	-	50	550
		LT255/75R17	111/108Q	C	BSW	360790	6.5-(7.0)-8.5	57	18.3	32.3	10.0	2405	2205	50	643
		LT255/80R17	121/118Q	E	BSW	361110	6.5-(7.0)-8.5	61	18.3	33.3	10	3195	2910	80	624
		LT265/70R17	121P	E	BSW	360130	7.0-(8.0)-8.5	59	18.9	32.0	10.8	3195	-	80	648
		LT285/70R17	121/118P	E	BSW	360650	7.5-(8.5)-9.0	64	18.9	33.0	11.5	3195	2910	80	630
		LT285/70R17	116/113Q	C	BSW	361100	7.5-(8.5)-9.0	65	18.9	33.0	11.5	2755	2535	50	630
		LT285/75R17 (34X11.50R17)	121P	E	BSW	360430	7.5-(8.0)-9.5	69	19.1	34.1	11.6	3195	-	80	608
		LT295/70R17 (33X11.50R17)	128P	E	BSW	360360	7.5-(8.5)-10.0	68	19.4	33.5	12.0	3970	-	80	619
		LT315/70R17	121/118Q	E	BSW	360780	8.0-(9.5)-11.0	78	20.2	34.6	12.7	3195	2910	65	600
		LT315/70R17	113/110Q	C	BSW	361150	8.0-(9.5)-11.0	76	20.2	34.6	12.7	2535	2335	35	600
		33X12.50R17LT	120Q	E	BSW	360760	8.5-(10.0)-11.0	71	21.0	32.8	12.5	3085	-	65	634
		35X12.50R17LT	125Q	E	BSW	360310	8.5-(10.0)-11.0	78	21.0	34.8	13.2	3640	-	65	596
	18		37X12.50R17LT	124Q	D	BSW	360770	8.5-(10.0)-11.0	84	21.0	36.8	12.5	3525	-	50
		37X13.50R17LT	131Q	E	BSW	360270	8.5-(11.0)	94	21.0	37.0	14.6	4300	-	65	560
		40X13.50R17LT	121Q	C	BSW	361010	8.5-(11.0)	104	21.0	39.7	14.4	3195	-	35	522
		LT265/70R18	124/121Q	E	BSW	361090	7.0-(8.0)-9.0	60	18.9	32.9	10.7	3525	3195	80	632
		LT275/65R18	123/120P	E	BSW	360620	7.5-(8.0)-9.0	63	18.9	32.3	11.0	3415	3085	80	643
		LT275/70R18 (33X11.00R18)	125P	E	BSW	360120	7.0-(8.0)-8.5	65	19.1	33.6	11.0	3640	-	80	617
		LT285/70R18 (34X11.50R18)	127/124Q	E	BSW	360590	7.5-(8.5)-9.5	70	18.9	34.1	11.4	3860	3525	80	609
		LT285/75R18 (35X11.5R18)	129P	E	BSW	360420	7.5-(8.0)-9.5	72	19.1	35.1	11.6	4080	-	80	591
		LT295/70R18	129/126P	E	BSW	360640	7.5-(8.5)-10.0	72	19.4	34.5	11.8	4080	3750	80	602
		LT305/65R18	128/125Q	F	BSW	361140	8.5-(9.0)-11.0	71	19.5	33.8	12.2	3970	3640	80	614
		LT315/70R18 (36X13.00R18)	127/124Q	E	BSW	360560	8.0-(9.5)-11.0	81	20.7	35.7	13.0	3860	3525	65	581
		33X12.50R18LT	118Q	E	BSW	360340	8.5-(10.0)-11.0	74	21.0	33.0	12.7	2910	-	65	630
		33X12.50R18LT	122Q	F	BSW	360810	8.5-(10.0)-11.0	74	21.0	32.8	12.5	3305	-	80	634
		35X12.50R18LT	123Q	E	BSW	360090	8.5-(10.0)-11.0	81	21.0	35.0	13.2	3415	-	65	593
	35X12.50R18LT	128Q	F	BSW	360820	8.5-(10.0)-11.0	81	21.0	34.8	12.5	3970	-	80	598	
	37X13.50R18LT	124Q	D	BSW	360300	8.5-(11.0)	90	21.0	37.0	14.2	3525	-	50	560	
	38x13.50R18LT	126Q	D	BSW	360380	8.5-(11.0)	92	21.0	37.7	14.3	3750	-	50	550	
	38X15.50R18LT	128Q	D	BSW	360180	11.0-(12.0)-13.0	103	21.0	37.7	15.9	3970	-	50	550	
20		LT275/55R20	115/112P	D	BSW	360670	7.5-(8.5)-9.5	64	19.1	32.1	11.2	2680	2470	65	647
		LT275/65R20 (34X11.00R20)	126P	E	BSW	360410	7.5-(8.0)-9.5	67	19.1	34.5	11.0	3750	-	80	601

Speed rated "P" = 93mph, "Q" = 99mph. "C" = 6-ply rating, "D" = 8-ply rating, "E" = 10-ply rating, "F" = 12-ply rating, "BSW" = Black Sidewall. Bold designates measuring rim width. *Inflated dimensions.

SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
20	LT285/60R20	125/122Q	E	BSW	361040	8.0-(8.5)-10.0	69	18.9	33.5	11.5	3640	3305	80	621
	LT295/55R20	123/120P	E	BSW	360610	8.0-(9.5)-10.0	68	19.4	33.0	12.2	3415	3085	80	630
	LT295/60R20	126/123P	E	BSW	360660	8.0-(8.5)-10.0	75	19.4	34.2	11.8	3750	3415	80	608
	LT295/65R20	129/126P	E	BSW	360630	8.0-(8.5)-10.0	72	19.4	35.4	11.8	4080	3750	80	588
	LT305/55R20	125/122Q	F	BSW	360870	8.5-(9.5)-11.0	70	19.5	33.5	12.4	3640	3305	80	621
	LT315/60R20 (35X12.50R20)	125Q	E	BSW	360510	8.5-(9.5)-11.0	78	20.7	35.0	12.6	3640	3305	65	593
	33X12.50R20LT	114Q	E	BSW	360330	8.5-(10.0)-11.0	73	21.0	33.0	12.6	2600	-	65	630
	33X12.50R20LT	119Q	F	BSW	360830	8.5-(10.0)-11.0	73	21.0	32.8	12.5	3000	-	80	634
	35X12.50R20LT	121Q	E	BSW	360240	8.5-(10.0)-11.0	79	21.0	35.0	13.0	3195	-	65	592
	35X12.50R20LT	125Q	F	BSW	360800	8.5-(10.0)-11.0	79	21.0	34.8	12.5	3640	-	80	598
	35X13.50R20LT	126Q	F	BSW	360860	9.5-(11.0)-12.0	78	21.0	34.8	13.6	3750	-	80	598
	37X12.50R20LT	126Q	E	BSW	360750	8.5-(10.0)-11.0	85	21.0	36.8	12.5	3750	-	65	565
	37X13.50R20LT	127Q	E	BSW	360220	8.5-(11.0)	92	21.0	37.0	14.0	3860	-	65	560
	38X15.50R20LT	124Q	D	BSW	360390	8.5-(11.0)	95	21.0	37.7	14.3	3525	-	50	550
	38X15.50R20LT	125Q	D	BSW	360190	11.0-(12.0)-13.0	101	21.0	37.7	15.9	3640	-	50	550
	40X15.50R20LT	130Q	D	BSW	360370	11.0-(12.0)-13.0	109	21.0	39.7	15.9	4190	-	50	522
22	LTR295/55R22	125/122Q	E	BSW	361130	8.0-(9.5)-10.5	74	19.5	35.0	12.2	3640	3305	80	594
	LT325/50R22	127Q	F	BSW	361120	9.0-(10.0)-12.0	73	20.2	35.1	13.2	3860	-	80	592
	LT325/50R22	122Q	E	BSW	360880	9.0-(10.0)-12.0	78	20.2	35.1	13.2	3305	-	65	592
	33X12.50R22LT	109Q	E	BSW	360520	8.5-(10.0)-11.0	65	18.9	33.0	12.4	2270	-	65	629
	33X12.50R22LT	114Q	F	BSW	360840	8.5-(10.0)-11.0	65	18.9	32.8	12.5	2600	-	80	634
	35X12.50R22LT	117Q	E	BSW	360540	8.5-(10.0)-11.0	73	21.0	35.0	12.8	2835	-	65	593
	35X12.50R22LT	121Q	F	BSW	360850	8.5-(10.0)-11.0	72	21.0	34.8	12.5	3195	-	80	598
	37X12.50R22LT	127Q	F	BSW	361050	9.0-(10.0)-11.5	86	21.0	36.8	12.5	3860	-	80	565
	37X13.50R22LT	123Q	E	BSW	360210	8.5-(11.0)	84	21.0	37.0	14.0	3420	-	65	560
	37X13.50R22LT	128Q	F	BSW	361160	8.5-(11.0)	85	21.0	36.8	13.6	3970	-	80	565
	38X15.50R22LT	128Q	E	BSW	360980	11.0-(12.5)-14.0	99	21.0	37.8	15.6	3970	-	65	550
	40X15.50R22LT	127Q	D	BSW	360200	11.0-(12.0)-13.0	109	21.0	39.7	15.9	3860	-	50	522
24	LT375/40R24	126Q	F	BSW	361170	12.5-(13.5)-15.0	90	19.5	36.1	15.2	3750	-	80	576
	37X13.50R24LT	120Q	E	BSW	360350	8.5-(11.0)	90	21.0	37.0	13.6	3085	-	65	561
	40X15.50R24LT	128P	E	BSW	360680	11.0-(12.0)-14.0	106	21.0	39.8	15.4	3970	-	65	522
26	40X15.50R26LT	126Q	E	BSW	360970	11.0-(12.5)-14.0	108	21.0	39.8	15.6	3750	-	65	522
	42X15.50R26LT	126Q	D	BSW	361190	11.0-(12.5)-14.0	110	21.0	41.8	15.6	3750	-	50	497



LIGHT TRUCK / SUV / CUV

LT