



RI-119 ECORUN

DESIGNED FOR EVEN WEAR AND DEPENDABLE ON-HIGHWAY SERVICE

TRAILER POSITION



11R22.5
11R24.5
295/75R22.5
285/75R24.5

The **RI-119 ECORUN** is packed with features not typically seen in a trailer position tire, including stone drilling defense for added casing protection. The cut-resistant tread compound and four steel belts help the tire resist cuts, chips, tearing, and irregular wear. The RI-119EC, with exceptional retreadability and an original low rolling resistance compound, delivers a cost-effective choice to any fleet.



DECOUPLING GROOVE
combats irregular wear and enhances tread life.



STONE DEFENSE FEATURES
effectively minimize rock and pebble packing to protect the belt package and casing from stone drilling.



FOUR STEEL BELTS
enhance puncture resistance and improve retreadability.



LOW ROLLING RESISTANCE TREAD COMPOUND
optimizes fuel economy and promotes long wear.

Size	Ply-Rating/ Load Range	Item #	Single Load Index	Dual Load Index	OD (in)	S.L.R. (in)	Buff Radius	Overall Width (in)	RPM	Tread Depth (in)	Weight		Max Speed (MPH)	Single Load Limit		Dual Load Limit	
											lbs.	kg		lbs./PSI	kg/kPa	lbs./PSI	kg/kPa
11R22.5	14/G	62582936	144	142	41.0	19.2	24	11.2	506	12/32	102	46	75	6175@105	2800@720	5840@105	2650@720
11R24.5	14/G	62582966	146	143	43.0	20.1	24	11.1	483	12/32	109	49	75	6610@105	3000@720	6005@105	2725@720
295/75R22.5	14/G	62582926	144	141	39.8	18.3	28	11.3	522	12/32	94	43	75	6175@110	2800@760	5675@110	2575@760
285/75R24.5	14/G	62582956	144	141	41.1	19.3	28	10.6	506	12/32	107	48	75	6175@110	2800@760	5675@110	2575@760

Product images are for illustrative purposes only. Tread design, technical information and tire construction subject to change without notice and may vary by size.