



RI120

REGIONAL SERVICE TIRE WITH HIGH MILEAGE CAPABILITY

ALL POSITION



10.00R20
11R22.5
12R22.5
11R24.5

12R22.5
255/70R22.5
285/75R24.5
295/75R22.5

The **RI120** is ideal for various all position usage from steer use in some sizes to spread axle trailers. The rounded shoulder profile combats side force wear experienced in spread axle applications and features a unique tread design that delivers even wear across the surface of the tire.



ROUNDED SHOULDER PROFILE
is ideal for spread axle applications.



WET WEATHER TRACTION
is achieved by two wide circumferential grooves to reduce hydroplaning tendency often experienced in wet weather conditions.



3-RIB TREAD DESIGN
promotes even wear by optimizing the tread void across the tire surface.



PREMIUM BASE RUBBER COMPOUND
designed to enhance retread capability.

Size	Ply-Rating/ Load Range	Item #	Single Load Index	Dual Load Index	OD (in)	S.L.R. (in)	Buff Radius	Overall Width (in)	RPM	Tread Depth (in)	Weight		Max Speed (MPH)	Single Load Limit		Dual Load Limit	
											lbs.	kg		lbs./PSI	kg/kPa	lbs./PSI	kg/kPa
10.00R20	14/G	62120846	144	142	41.5	19.4	22	10.9	501	15/32	121	55	75	6175@105	2800@720	5840@105	2650@105
11R22.5	16/H	62120937	148	145	41.5	19.4	22	10.8	501	19/32	113	51	81	6610@120	3000@830	6005@120	2725@830
11R24.5	16/H	62120969	149	146	43.4	20.3	22	10.9	478	19/32	122	55	75	7160@120	3250@830	6610@120	3000@830
12R22.5	16/H	62120947	152	148	42.6	19.8	24	11.7	488	19	132	60	81	7390@120	3350@830	6780@120	3075@830
255/70R22.5	16/H	62120706											75				
285/75R24.5	16/H	62120956											75				
295/75R22.5	16/H	62120926											75				

Product images are for illustrative purposes only. Tread design, technical information and tire construction subject to change without notice and may vary by size.