




RI151

REGIONAL SERVICE TIRE WITH HIGH MILEAGE CAPABILITY

ALL POSITION

215/75R17.5
235/75R17.5
225/70R19.5
245/70R19.5

265/70R19.5
245/75R22.5
295/80R22.5
315/80R22.5
385/65R22.5



The **RI151** tire is built with a wide tread surface for a stable drive to boost driver confidence. An innovative tread compound adds high mileage capability to minimize tire maintenance, and wide outside shoulder ribs were designed to help prevent irregular wear. This regional-use tire was created to deliver dependable service for a wide range of on-highway applications.



OPTIMIZED FOOTPRINT

promotes even wear by completely redesigning the footprint shape, evenly distributing contact pressure for long, even wear.



STONE DEFENSE FEATURES

effectively minimize rock and pebble packing to protect the belt package and casing from stone drilling.



WIDE OUTSIDE SHOULDER GROOVES

improve on-road stability for enhanced driver confidence and tread life by distributing the load across a wider tread surface.



HIGH-QUALITY BASE RUBBER COMPOUND

for optimal retreadability.

Size	Ply-Rating/ Load Range	Item #	Single Load Index	Dual Load Index	OD (in)	S.L.R. (in)	Buff Radius	Overall Width (in)	RPM	Tread Depth (in)	Weight		Max Speed (MPH)	Single Load Limit		Dual Load Limit	
											lbs.	kg		lbs./PSI	kg/kPa	lbs./PSI	kg/kPa
215/75R17.5	16/H	62151001	135	133	30.4	14.3	16	8.4	685	15/32	59	27	75	4805@123	2180@850	4540@123	2060@850
235/75R17.5	18/J	62151726	143	141	31.4	14.7	18	9.5	662	17/32	66	30	60	6005@127	2725@875	5675@127	2575@875
225/70R19.5	14/G	62151705	128	126	31.9	14.9	20	8.8	652	16/32	64	29	75	3970@110	1800@760	3750@110	1700@760
245/70R19.5	16/H	62151716	136	134	33.1	15.4	22	9.6	627	16/32	76	34	75	4940@120	2240@825	4675@120	2120@825
265/70R19.5	16/H	62151267	143	141	34.1	15.9	22	10.0	608	16/32	60	27	75	6005@123	2725@850	5675@123	2575@850
245/75R22.5	14/G	62151906	134	131									75	4675@110	2120@760	4300@110	1950@760
295/80R22.5	16/H	62151987	152	148	41.4	19.2	24	12.1	501	20/32	133	60	75	7830@123	3550@850	6940@123	3150@850
315/80R22.5	18/J	62151949	156	150	42.3	19.6	24	12.4	491	19/32	141	64	75	8820@123	4000@850	7390@123	3350@850
385/65R22.5	20/L	62151919	160K	(158L)	42.3	19.5	32	14.9	495	18/32	163	74	75	9920@130	4500@900		

Product images are for illustrative purposes only. Tread design, technical information and tire construction subject to change without notice and may vary by size.