





GOODYEAR® RT-3B

CENTERLINE LUGS AND OPEN SHOULDER provide cut resistance while maintaining traction

115-LEVEL TREAD DEPTH promotes low heat generation and long hours to removal

HI-STABILITY TECHNOLOGY stiffens the sidewall to reduce bucket sway and increase driver confidence in loading operations[†]

RADIAL CONSTRUCTION promotes a softer ride, improved treadwear and enhanced durability

HIGH-TENSILE STEEL BELT PACKAGE offers cut resistance and enhances retreadability

†Available in 23.5R25, 26.5R25 and 29.5R25 only

PERFORMANCE*

Abrasion/Cut Resistance	Heat Resistance	Traction	Stability		
7	8	8	8		
Self Cleaning	Longevity	Comfort			
7	6	8			

‡As compared to other Goodyear L3/G3 tires

ENGINEERING DATA										
DIMENSION	RIM WIDTH / FLANGE HEIGHT (in)	TREAD DEPTH (mm / 32nds)	OVERALL WIDTH (mm / in)	OVERALL DIAMETER (mm / in)	STATIC LOADED RADIUS (mm / in)					
17.5R25	14.00 / 1.5	29 / 36	460 / 18.1	1,351 / 53.2	603 / 23.7					
20.5R25	17.00 / 2.0	32 / 41	544 / 21.4	1,486 / 58.5	673 / 26.5					
23.5R25 (HI-STABILITY)	19.50 / 2.5	35 / 44	640 / 25.2	1,605 / 63.2	710 / 27.9					
26.5R25 (HI-STABILITY)	22.00 / 3.0	40 / 50	695 / 27.4	1,741 / 68.6	765 / 30.1					
29.5R25 (HI-STABILITY)	25.00 / 3.5	44 / 55	760 / 29.9	1,857 / 73.1	823 / 32.4					

LOADS & INFLATION for slow speed service at 10 km/h (5 mph) maximum speed

LOAD PER TIRE IN KG / LBS AT INFLATION BAR / KPA / PSI

DIMENSION	STAR Marking	LOAD Speed index	2.00 / 200 / 29	2.50 / 250 / 36	3.00 / 300 / 44	3.50 / 350 / 51	4.00 / 400 / 58	4.50 / 450 / 65	5.00 / 500 / 73	5.50 / 550 / 80	5.75 / 575 / 83	6.25 / 625 / 91	6.50 / 650 / 94
17.5R25	*	176 A2	3,650 / 8,050	4,250 / 9,350	4,850 / 10,700	5,600 / 12,300	6,000 / 13,200	6,500 / 14,300	7,100 / 15,700*	_	_	_	_
20.5R25	*	186 A2	4,750 / 10,500	5,600 / 12,300	6,300 / 13,900	7,100 / 15,700	8,000 / 17,600	8,750 / 19,300	9,500 / 20,900*	_	_	_	_
23.5R25	**	201 A2	6,000 / 13,200	7,100 / 15,700	8,250 / 18,200	9,250 / 20,400	10,300 / 22,700	11,200 / 24,700	12,150 / 26,800*	12,850 / 28,300	13,200 / 29,100	14,000 / 30,900	14,500 / 32,000**
26.5R25	**	209 A2	7,500 / 16,500	9,000 / 19,800	10,300 / 22,700	11,500 / 25,400	12,850 / 28,300	14,000 / 30,900	15,000 / 33,100*	16,000 / 35,300	16,500 / 36,400	18,000 / 39,700	18,500 / 40,800**
29.5R25	**	216 A2	_	_	_	_	15,500 / 34,200	17,000 / 37,500	18,000 / 39,700*	19,500 / 43,000	20,000 / 44,100	21,200 / 46,700	22,400 / 49,400**

LOADS & INFLATION for off-the-road tractor and grader service at 40 km/h (25 mph) maximum speed

LOAD PER TIRE IN KG / LBS AT INFLATION BAR / KPA / PSI

DIMENSION	STAR Marking	LOAD SPEED Index	1.25 / 125 / 18	1.50 / 150 / 22	1.75 / 175 / 25	2.00 / 200 / 29	2.25 / 225 / 33	2.50 / 250 / 36	2.75 / 275 / 40	3.00 / 300 / 44
17.5R25	*	153 A8	_	_	2,360 / 5,200	2,575 / 5,680	2,900 / 6,400	3,075 / 6,800	3,350 / 7,400	3,650 / 8,050*
20.5R25	*	161 A8	_	_	3,150 / 6,950	3,450 / 7,600	3,825 / 8,550	4,125 / 9,100	4,375 / 9,650	4,625 / 10,200*
23.5R25	**	170 A8	_	_	4,000 / 8,800	4,500 / 9,900	4,875 / 10,700	5,300 / 11,700	5,600 / 12,300	6,000 / 13,200*
26.5R25	**	178 A8	3,875 / 8,550	4,500 / 9,900	5,000 / 11,000	5,600 / 12,300	6,150 / 13,600	6,700 / 14,800	7,100 / 15,700	7,500 / 16,500*



Trusted Products

Specialized OTR Innovations to Help Lower Operating Costs



Reliable Services

Expert Worldwide Support to Help You Optimize Operations



Tire Management Solutions

Value-Added Tools to Help Grow Your Business with Confidence

To learn more about the Goodyear RT-3B, contact your local authorized Goodyear Dealer.



