


PREMIUM, DURABLE PERFORMANCE FOR DEMANDING REGIONAL HAUL AND IN-CITY APPLICATIONS

Durability and high performance under the toughest regional haul and in-city conditions are the hallmarks of the RY023. This sure-footed, five-rib, all-position workhorse features a tough band of additional rubber that protects the sidewall from scrubbing damage caused by curbing and other regional haul and in-city application abuses.

Enhanced Durability

Rock-Ejector Platforms keep stones and debris out of the grooves to help thwart irregular wear and enhance durability.



Rock-Ejector Platforms


Sidewall Abrasion Guard, a tough band of additional rubber, reduces damage to the sidewall caused by curbing and other accidental scrubbing.



Sidewall Abrasion Guard

Long Wearing Design


Five-rib Tread Pattern with semi-rounded shoulders reduces the potential for shoulder ripping and tearing while enhancing lateral stability, water dispersion and overall traction.



Tread Pattern

Mounting Ease

Hexagonal Bead Base allows for easier mounting and even pressure along the entire circumference of the wheel for smooth rolling as well as increased driver comfort.



Hexagonal Bead

PURE YOKOHAMA TECHNOLOGY

RY023 is equipped with the best Yokohama premium design concepts to meet stringent, modern fleet performance demands.



RYO23

SPECIFICATIONS

Tire Size	Ply Rating (L.R.)	Rim Size		Inflated Dimensions			Loaded Dimensions			Rev/Mile	Part #
		Meas.	Alt	Overall Width (Inch)	Overall Diameter (Inch)	Groove Depth (1/32")	Section Width (Inch)	Static Radius (Inch)			
215/75R17.5	16H	6.00	6.00 - 6.75	8.5	30.6	16	9.1	14.2	674	02385	
235/75R17.5	16H	6.75	6.75 - 7.50	9.4	31.7	16	10.0	14.6	661	02386	
225/70R19.5	12F	6.75	6.00	8.7	31.8	16	9.4	14.8	652	02389	
245/70R19.5	14G	7.50	6.75	9.7	33.3	16	10.4	15.5	628	02399	
265/70R19.5	14G	7.50	8.25	10.3	34.3	17	11.1	15.8	612	02398	
285/70R19.5	16H	8.25	7.50 - 9.00	11.1	35.1	17	12.1	16.3	597	02397	
255/70R22.5	16H	7.50	8.25	10.1	36.6	18	10.7	17.1	570	02387	
295/75R22.5	14G	9.00	8.25	11.1	40.2	19	12.1	18.7	520	02396	
295/75R22.5	16H	9.00	8.25	11.1	40.2	19	12.1	18.7	520	02391	
11R22.5	14G	8.25	7.50	10.8	41.4	19	12.0	19.3	504	02395	
11R22.5	16H	8.25	7.50	10.8	41.4	19	12.0	19.3	504	02392	
12R22.5	16H	9.00	8.25	11.5	42.7	20	12.8	19.8	490	02388	
285/75R24.5	14G	8.25	...	10.9	41.4	19	11.8	19.2	503	02390	
11R24.5	14G	8.25	7.50	10.7	43.4	19	11.9	20.0	483	02393	
11R24.5	16H	8.25	7.50	10.7	43.4	19	11.9	20.0	483	02394	

Yokohama tires are subject to an ongoing development process. Yokohama Tire Corporation reserves the right to change product specifications at any time without notice or obligation. Not all models and sizes available in all locations.

Corporate Headquarters
P.O. Box 4550
Fullerton, California 92834-4550
800.423.4544
714.870.3800

Commercial Customer Service
For Dealer Orders Call: 800.241.7051
Dealer Fax Orders: 800.455.9656
770.932.0560

Consumer Affairs
800.722.9888

Remember to register your Yokohama tires either on-line at yokohamatire.com or by mail. Mail-in registration cards are available at authorized Yokohama dealers.



www.yokohamatire.com

M-331-0507