

HIGH-VALUE, HIGHWAY LINE-HAUL, ALL-POSITION TIRE

Yokohama has earned a reputation as a reliable performer with products that have been regarded as an exceptional value. The RY617 has all the traditional Yokohama qualities that savvy buyers have come to rely upon, along with the latest features that deliver long, even wear, enhanced wet traction and durability. The RY617 is everything you've come to appreciate in a Yokohama high-value, all-position tire and more.

Confident Handling


Our revered **five-rib tread design** is the perfect all-position high performer. Now enhanced with over 6,000 sipes, this premium feature provides excellent water evacuation and uniform wear. The **stress control sipes** are also especially effective in combating river wear.



Five-Rib Tread Design &
6,000+ SC Sipes


Long Even Wear

The **special contoured design of the groove walls** provides added rib stiffness that further combats uneven treadwear.



Variable Contour Groove Wall

Stress Wear Control Groove (SCG) reduces contact pressure at the tread edge, providing increased resistance to shoulder step down wear and enhancing long even wear, particularly at the shoulder area.



Stress Wear Control Groove

Built-in Stone Protection

Stone ejectors deep inside the tread grooves keep stones from imbedding into the tire to minimize drill damage for increased tread durability and casing life.



Stone Ejectors

PURE YOKOHAMA TECHNOLOGY

RY617 is equipped with many of the latest Yokohama design concepts to meet stringent, modern fleet performance demands.



Our Maintenance Saving Concept significantly reduces tire maintenance time and costs for today's fleets through the ingenious integration of six unique design elements.



RY617

SPECIFICATIONS



Tire Size	Ply Rating (L.R.)	Rim Size		Inflated Dimensions			Loaded Dimensions			Part #
		Meas.	Alt	Overall Width (Inch)	Overall Diameter (Inch)	Groove Depth (1/32")	Section Width (Inch)	Static Radius (Inch)	Rev/Mile	
295/75R22.5	14G	9.00	8.25	10.9	40.1	18	12.0	18.7	520	61701
11R22.5	14G	8.25	7.50	11.1	41.3	18	12.0	19.5	502	61702
285/75R24.5	14G	8.25	...	10.8	41.3	18	11.8	19.8	499	61703
11R24.5	14G	8.25	7.50	11.1	43.3	18	12.0	20.2	481	61704

Yokohama tires are subject to an ongoing development process. Yokohama Tire Corporation reserves the right to change product specifications at any time without notice or obligation. Not all models and sizes available in all locations.



Corporate Headquarters
 P.O. Box 4550
 Fullerton, California 92834-4550
 800.423.4544
 714.870.3800

Commercial Customer Service
 For Dealer Orders Call: 800.241.7051
 Dealer Fax Orders: 800.455.9656

Consumer Affairs
 800.722.9888

Remember to register your Yokohama tires either online at yokohamatire.com or by mail. Mail-in registration cards are available at authorized Yokohama dealers.



www.yokohamatire.com

M-307-1007