






## **Tire Structure**



# SMART FLEX DL15 SMARTWAY PENDING

Fuel Efficient and Optimized Traction Performance for Long and Regional Haul





Minimized motion of belts for reduced heat generateion. Wide Belt increases casing life.

#### **Carcass structure**

Minimized tire deformation for optimized foot shape and lower energy loss.



superior retreadability.


DL15


# Sizes and Specifications

Sizes and Specifications																
S-Code	Size	Ply Rating	Туре	Measuring Rim	Max. Air (PSI)		Max. Load (LBS)		Diameter	Width	Width	Depth			Speed	
					S	D	S	D	(inch)	(incn)	(incn)	(32nds)			(MPH)	
3002908	295/75R22.5	14	T/L	8.25	110	110	6,175	5,675	40.7	11.5	9.6	26	513	19.0	75	129
	11R22.5 **	14														
	11R22.5 **	16														
	11R24.5 **	14														
	11R24.5 **	16														
	285/75R24.5 **	14														

<sup>\*</sup> Technical data subject to change without prior notice.

# **Recommended Vehicle Types and Position**







Recommended position



#### Hankook Tire America Headquarters

333 Commerce Street, Suite 600 Nashville, Tennessee 37201, USA Tel: 1-615-432-0700 Fax: 1-615-242-8709

hankooktire.com/us

<sup>\*\*</sup> Sizes expected to be available later in the year

## Fuel Efficient and Optimized Traction Performance for Long and Regional Haul



#### Experience Smartec

Newly launched 'Smartec' is an integrated package of Hankook truck and bus tire technology. Smartec is based on five main tire performance factors featuring safety, mileage, anti chip & cut, retreadability, and traction. The technology provides a range of benefits that consumers identify as a key factor when selecting tires. Smartec is applied to the entire research, development and manufacturing process for all products.

## **Design Features and Technology**

### **Zigzag Groove**



Main four zigzag grooves deliver great traction performance.

#### Rib+Semi Lug



Combined structure of rib and semi block pattern provides excellent stability, mileage and handling.

#### **Wide Closed Shoulder**




Enhances stability and fuel efficiency allowing smooth wear.

#### **3D Siping: Zigzag Type**



Delivers even wear reinforcing inter-locking between blocks.

#### **Test Results**





#### **Bottom Round Edge Siping**

Round at the end of sipe prevents crack and tearing.





#### **Siping Depth**

[unit: 32nds]



Position	SMART ELEX DL12	SMART EEN DL15				
Center	10	21, 12, 19				
Rib	10	12, 19, 12				

<sup>\*</sup> Based on 295/75R22.5 size

## **Self-Regenerating Siping**



Turns out as groove at the mid and latter stage of use and it keeps excellent traction until the end of wear.

