

ON/OFF-ROAD HEAVY-DUTY ALL POSITION TIRE

The M325 is the cornerstone of our construction line. It provides full coverage for mixed service fleets serving the construction, mining, energy, and logging industries. A tough casing developed through several years of real-world testing in severe duty applications, a wide footprint with specially designed stone ejectors in every groove, and a cut-and-chip resistant tread compound deliver durability, retreadability and a high return on investment.

| APPLICATION | RECOMMENDED | SUITABLE |
|-------------|----------------|----------|
| URBAN | STEER, TRAILER | DRIVE |
| ON/OFF-ROAD | STEER, TRAILER | - |



M325

MAXIMUM REMOVAL MILES

- Durable cut-and-chip resistant tread compound extends tire life.

EXCELLENT PERFORMANCE AND SAFETY

- Wide footprint with deep tread provides traction and stability in severe duty applications.

EXCELLENT RETREADABILITY AND CASING DURABILITY

- Specially designed stone ejectors in every groove minimize casing damage.
- Tough casing developed with e-balance technology minimizes growth of the tread profile and maintains a uniform and flatter tread radius for the entire life of the casing.

| TIRE SIZE | PRODUCT CODE | LOAD RANGE & PLY RATING | LI/SS | APPROVED RIM WIDTH RANGE (IN.) (DESIGN RIM) | TIRE WEIGHT (LBS.) | TREAD DEPTH | INFLATED DIMENSIONS* | | STATIC LOADED RADIUS (IN.) | MAX LOAD (LBS.) | | MAX PRESSURE (LBS.) | | REVS PER MILE | MAX SPEED (MPH) |
|-----------|--------------|-------------------------|----------|---------------------------------------------|--------------------|-------------|------------------------|---------------------|----------------------------|-----------------|------|---------------------|------|---------------|-----------------|
| | | | | | | | OVERALL DIAMETER (IN.) | OVERALL WIDTH (IN.) | | SINGLE | DUAL | SINGLE | DUAL | | |
| 11R24.5 | 546190 | H / 16 | 149/146K | 7.50-(8.25) | 141 | 25 | 43.9 | 11.1 | 19.8 | 7160 | 6610 | 120 | 120 | 473 | 68 |