

TY303

APPLICATION

Deep tread drive-axle workhorse for on-highway operations.

Ideal for 2- or 3-axle tractors and available in low-profile sizes, the TY303 delivers long mileage, increased fuel economy and excellent retreadability.

SPECIAL FEATURES & BENEFITS

Advanced Shoulder Lug Groove Pattern promotes flat, even treadwear throughout the long life of the tire.

Special Tread Compound extends tire mileage and enables increased fuel economy.

Precise Casing Construction enables excellent retreadability.

Deep Tread Depth combined with a Rib-block design provides exceptional traction on snow and muddy terrain.



Tire Size	Part Number	Ply Rating (L.R.)	Rim Size		Inflated Dimensions		Tread Depth (1/32")	Loaded Dimensions			Max Load at Cold Inflation Pressure	
			Meas.	Alt.	Overall Width (inch)	Overall Diameter (inch)		Section Width (inch)	Static Radius (inch)	RPM	LB/PSI Single	LB/PSI Dual
295/75R22.5	30301	14G	9.00	8.25	11.4	40.7	28	12.3	19.0	513	6175@110	5675@110
11R22.5	30303	14G	8.25	7.50	11.1	42.0	28	12.2	19.6	497	6175@105	5840@105
285/75R24.5	30305	14G	8.25	--	10.9	42.0	28	11.7	19.7	496	6175@110	5675@110
11R24.5	30304	14G	8.25	7.50	11.1	44.0	28	12.2	20.6	474	6610@105	6005@105
255R/70R22.5	30312	16H	7.50	8.25	10.0	37.0	24	10.8	17.3	563	5510@120	5070@120
225/70R19.5	30319	12F	6.75	6.00	8.7	32.0	20	9.4	15.0	651	3640@95	3415@95
265/70R19.5	30315	14G	7.50	8.25	10.3	34.4	21	11.2	16.0	607	5070@110	4675@110
285/70R19.5	30316	16H	8.25	7.5 - 9.0	11.1	35.4	21	12.1	16.4	591	6395@120	6005@120

Technical information subject to change without notice.

YOKOHAMA TIRE CORPORATION
Corporate Headquarters
P.O. Box 4550
Fullerton, CA 92834-4550

Visit our web site at: www.yokohamatire.com



TECHNOLOGY THAT DELIVERS™